


GENERAL PURPOSE WATER ACCOUNTING REPORT

Gwydir Catchment

2020–21



Published by NSW Department of Planning and Environment

dpie.nsw.gov.au

Title: General Purpose Water Accounting Statement | Gwydir Catchment

Year: 2020–21 ISSN: 2652-5038

Department reference number: PUB22/351

More information

This report may be cited as NSW Department of Planning and Environment (2022) *General Purpose Water Accounting Report 2020–21: Gwydir Catchment*, NSW Department of Planning and Environment.

Acknowledgements

Produced by the Water Information team, NSW Department of Planning and Environment—Water group

© State of New South Wales through Department of Planning and Environment 2022. You may copy, distribute, display, download and otherwise freely deal with this publication for any purpose, provided that you attribute the Department of Planning and Environment as the owner. However, you must obtain permission if you wish to charge others for access to the publication (other than at cost); include the publication in advertising or a product for sale; modify the publication; or republish the publication on a website. You may freely link to the publication on a departmental website.

Disclaimer: The information contained in this publication is based on knowledge and understanding at the time of writing (March 2022) and may not be accurate, current or complete. The State of New South Wales (including the NSW Department of Planning and Environment), the author and the publisher take no responsibility, and will accept no liability, for the accuracy, currency, reliability or correctness of any information included in the document (including material provided by third parties). Readers should make their own inquiries and rely on their own advice when making decisions related to material contained in this publication.

Contents

Acknowledgment of Country	1
Director's foreword	2
Contextual statement	3
Accounting extent	4
Snapshot	6
Climate	
Dam inflows and volume	
Inflows	10
Storage volume	11
Major flow events	12
Surface water resources and management	13
Legislation	13
Access rights	13
Allocation account summary	14
Access licence account management	15
Extreme events stage and temporary water restrictions	16
Water availability	18
Account usage	21
Utilisation and inactive share	22
Temporary trading (allocation assignments)	23
Permanent trading (assignment of share and transfer of licence)	
Replenishment flows	27
Held environmental water	
Planned environmental water—environmental contingency allowance	29
Planned environmental water—other	29
Vater accounting statements	31
Significant water accounting policies	32
Quantification of data	32
Data accuracy	32
2020-21 Gwydir physical flows mass balance diagram	
Statement of water assets and water liabilities	
Changes in water assets and water liabilities	
Note disclosures	
Reconciliation and future prospect descriptions	
Note 1—Allocation accounts	
Note 2—Available water determination (AWD) (allocation announcement)	
Note 4—Internal trading (allocation assignments)	

	Note 5—Held environmental water	. 54
	Note 6—Environmental provisions	. 57
	Note 7—Surface water storage	. 59
	Note 8—River channel storage	60
	Note 9—Storage inflow—Copeton	. 61
	Note 10—Storage evaporation and storage rainfall	62
	Note 11—River evaporation and river rainfall	63
	Note 12—Gauged tributary inflow	65
	Note 13—Ungauged runoff estimate	67
	Note 14—Dam releases, river inflow from dam releases	69
	Note 15—End-of-system flow/flow to wetlands/replenishments	. 70
	Note 16—Extractions from river	. 73
	Note 17—Basic rights extractions	. 74
	Note 18—Supplementary extractions	. 75
	Note 19—Unaccounted difference	. 82
	Note 20—River and groundwater interaction	. 84
	Note 21—Water order debiting	. 86
	Note 22—Adjusting entry	. 87
R	eferences	. 88

Abbreviations

Abbreviation/acronym	Description
ARCGIS	mapping and spatial analysis platform for designing and managing solutions through the application of geographic knowledge
AWAS 1	Australian Water Accounting Standard 1
AWD	available water determination
BoM	Bureau of Meteorology
CAIRO	computer-aided improvements to river operations
ECA	environmental contingency allowance
GIS	geographic information system
GPWAR	general purpose water accounting report
IQQM	integrated quantity and quality model
MDBA	Murray–Darling Basin Authority
ML	megalitres (1,000,000 litres)
ML/d	megalitres per day
MODFLOW	modular, 3-dimensional, finite-difference groundwater flow model
SILO	climatic data provision system run by the Queensland Government for the provision of both measured and modelled data
WASB	Water Accounting Standards Board
WaterNSW	WaterNSW is a New South Wales Government–owned statutory corporation that is responsible for supplying the state's bulk water needs, and operating the state's river systems and dams
WSP	water sharing plan

Glossary

Term	Meaning
allocation	the specific volume of water allocated to water allocation accounts in a given season, defined according to rules established in the relevant water plan
allocation assignments	the transfer of water between licence holder allocation accounts as a result of a trade agreement The assignment becomes part of the receiver's current year allocation account water.
allocation account	water account attached to an access licence used to track the balance of account water
available water determination (AWD)	the process by which water is made available for use and shared amongst water users who hold a water access licence It determines the volume of water that is to be added to an individual's licence allocation account.
Australian Water Accounting Standard (AWAS)	a national standard that prescribes the basis for preparing and presenting a general-purpose water accounting report (GPWAR) It sets out requirements for the recognition, quantification, presentation and disclosure of items in a GPWAR.
back-calculation	a calculation approach using a mass balance to determine an unknown variable (used to calculate storage inflows based on balancing the change in storage volume where inflow is the only unknown)
basic rights	the non-licensed right to extract water to meet basic requirements for household purposes (non-commercial uses in and around the house and garden) and for watering of stock It is available for anyone who has access to river frontage on their property.
computer aided improvements to river operations (CAIRO)	a spreadsheet-based water balance model used for optimising river operations (orders and releases)
carryover	the volume or share component that may be reserved by a licence holder for use in the subsequent year
catchment	the areas of land that collect rainfall and contribute to surface water (streams, rivers, wetlands) or to groundwater A catchment is a natural drainage area, bounded by sloping ground, hills or mountains, from which water flows to a low point.
dead storage	the volume in storage that is generally considered unavailable for use (e.g. water level below release valves) due to access and often poor water quality
effective storage	the total volume of storage minus the dead storage component—the volume generally considered as useable
effluent	flow leaving a place or process Sewage effluent refers to the flow leaving a sewage treatment plant. An effluent stream is one which leaves the main river and does not return.
entity	a defined geographical area or zone within the accounting region Transactions and reports are produced for each entity.
end of system	the last defined point in a catchment where water information can be measured and/or reported

Term	Meaning
environmental water	water allocated to support environmental outcomes and other public benefits
	Environmental water provisions recognise the environmental water requirements and are based on environmental, social and economic considerations, including existing user rights.
evaporation	the process by which water or another liquid becomes a gas
	Water from land areas, bodies of water, and all other moist surfaces is absorbed into the atmosphere as a vapour.
evapotranspiration	the process by which water is transmitted as a vapour to the atmosphere as the result of evaporation from any surface and transpiration from plants
extraction	the pumping or diverting of water from a river or aquifer by licensed users for a specific purpose (irrigation, stock, domestic, towns, etc.)
	The volume is measured at the point of extraction or diversion (river pump, diversion works, etc.).
general purpose water	a report prepared according to the Australian Water Accounting Standard
accounting report (GPWAR)	It comprises a number of components including a contextual statement, a statement of water assets and water liabilities, a statement of change in water assets and water liabilities, a statement of physical water flows, notes and disclosures, and an assurance and accountability statement.
general-security licence	a category of water access licence implemented under the Water Management Act 2000
	This forms the bulk of the water access licence entitlement volume in NSW and is a low-priority entitlement (i.e. it only receives water once essential and high-security entitlements are met in the available water determination process).
groundwater	water location beneath the ground in soil pore spaces and in the fractures of rock formations
high-security licence	a category of water access licence implemented under the Water Management Act 2000
	It receives a higher priority than general-security licences but less priority than essential requirements in the available water determination process.
HYDSTRA database	a database used by NSW Department of Planning and Environment to store continuous, time-series data such as river flow, river height, and water quality
inflows	surface water runoff and deep drainage to groundwater (groundwater recharge) and transfers into the water system (both surface and groundwater) for a defined area
inter-valley trade	trade of licence holder allocation account water via allocation assignment from one catchment to another catchment (or state)
intra-valley trade	trade of licence holder allocation account water via allocation assignment within the same catchment
median	the middle point of a distribution, separating the highest half of a sample from the lowest half
non-physical transaction	an accounting transaction representing a process that is not a component of the water cycle (e.g. an available water determination)
physical transaction	an accounting transaction representing a process of the water cycle (e.g. an extraction)

Term	Meaning
regulated river	a river system where flow is controlled via one or more major man-made structures such as dams and weirs
	For the purposes of the <i>Water Management Act 2000</i> , a regulated river is one that is declared by the minister to be a regulated river. Within a regulated river system, licence holders can order water against a held entitlement.
share component	an entitlement to water specified on the access licence, expressed as a unit share or, in the case of specific purpose licences (e.g. local water utility, major water utility and domestic and stock), a volume in megalitres
	The amount of water a licence holder is allocated as a result of an available water determination and the amount they can take in any year is based on their share component.
storage	a state-owned dam, weir or other structure that is used to regulate and manage river flows in the catchment and the water bodies impounded by these structures
storage reserve	proportion of water in a storage reserved in the resource assessment process for future essential or high-security requirements (e.g. town water)
storage volume	the total volume of water held in storage at a specified time
supplementary water	unregulated river flow available for extraction under a supplementary licence
surface water	all water that occurs naturally above ground including rivers, lakes, reservoirs, creeks, wetlands and estuaries
tributary	a smaller river or stream that flows into a larger river or stream Usually, several smaller tributaries merge to form a river.
ungauged catchment	a catchment without a flow gauge to accurately record stream flows Modelled estimates must be used to approximate the contribution of ungauged catchments to the main river.
water accounting	the systematic process of identifying, recognising, quantifying, reporting, assuring and publishing information about water, the rights or other claims to that water, and the obligations against that water
water assets	the physical water held in storage, as well as any claims to water that are expected to increase the future water resource (e.g. external water entering the system through inter-valley trading)
water liabilities	claims on the water assets of the water report entity, including water that has been allocated to licence holder accounts or environmental accounts, yet to be taken at the end of the reporting period
water sharing plan	a water management plan that defines the rules for sharing of water within a region under the Water Management Act 2000

Acknowledgment of Country

NSW acknowledges Aboriginal people as Australia's First Peoples practicing the oldest living culture on earth and as the Traditional Owners and Custodians of the lands and waters on which we rely.

We acknowledge the people of the Gomeroi/Kamilaroi Nation hold the land and waters of the Gwydir River catchment area is of spiritual, cultural, customary and economic importance.

We recognise the intrinsic connection of Traditional Owners to Country and acknowledge their contribution to the management of the Gwydir River catchment landscape and natural resources.

Director's foreword

This is the eleventh annual release of the general-purpose water accounting report (GPWAR) for the Gwydir Regulated River Water Source. It has been prepared for the accounting period 1 July 2020 to 30 June 2021 (reporting period), under the Australian Water Accounting Standard 1 (WASB, 2012).

The GPWAR provides stakeholders with a consolidated, comparable and publicly accessible set of water accounting information for the water source. The information presented is also used internally for a range of water planning functions and legislative reporting obligations.

Included in the GPWAR are:

- a contextual statement, summarising the climatic conditions, water resources, environmental holdings, water trading market and water resource management in the water source for the reporting period
- a physical flow diagram, illustrating changes in storage volumes and the associated inflows and outflows
- water accounting statements presenting the opening and closing balances, and itemised changes to these balances for available water resources (water assets) and licenced allocation accounts (water liabilities)
- disclosure notes (linked to the figures within the water accounting statements) providing detailed information of accounting components including:
 - access licence account balances
 - o planned and held environmental water account balances
 - a detailed available water determination report
 - o temporary trading by licence category
 - o supplementary announcements and usage by river reach
 - o physical inflows and outflows to the system for the water year.

Where possible, we have provided quantification of the physical groundwater interactions with the regulated river water source. However, we have not included detailed groundwater accounting information in this GPWAR.

As Director Water Analytics, NSW Department of Planning and Environment, I declare:

- the information presented in these accounts as a faithful representation of the management and operation of the Gwydir Regulated River Water Source for the reporting period
- all data presented in this report is based on the best available information at the time of publication
- NSW Department of Planning and Environment has, to the best of its ability, prepared this GPWAR in accordance with the Australian Water Accounting Standard 1.

Danielle Baker

Director Water Analytics

NSW Department of Planning and Environment

Contextual statement

The Gwydir River is part of the Murray–Darling drainage basin in northern NSW. Covering an area of 26,600 square kilometres, the catchment extends 670 kilometres from the Great Dividing Range to the Barwon River near Collarenebri. It is separated from the Border Rivers catchment to the north by the Mastermans Range and from the Namoi catchment to the south by the Nandewar Range.

From its headwaters near Guyra and Uralla, around 1,200 metres above sea level, the Gwydir River flows north-west through steep-sided valleys. It is joined by the Horton River, the largest tributary flowing north from the Nandewar Range, before it enters the alluvial plains near Gravesend. West of Pallamallawa, the valley widens into an almost completely flat floodplain where the elevation is generally less than 200 metres. Through this flat landscape, the Gwydir flows slowly westward between low natural levee banks towards the Barwon River.

Downstream of Moree is an alluvial fan covering 200 square kilometres, where extensive floodplain wetlands known as the Lower Gwydir Wetlands have developed. These wetlands provide valuable habitat for waterbirds and are listed as a site of international significance under the Ramsar Convention on Wetlands of International Importance.

The lower half of the basin is characterised by numerous anabranches and effluents, the most significant being the Mehi River and Moomin Creek to the south, and the Carole-Gil Gil Creek system to the north.

The dominant land uses in the valley are livestock grazing and dryland agriculture, which together cover 90% of the catchment. The self-mulching black soils of the lower valley have been extensively developed for irrigated agriculture. Around 1,000 square kilometres is used to grow crops such as cotton, cereals and oilseeds.

Most of the summer crops such as cotton are irrigated, while much of the winter demand is met by rainfall. Irrigation water, town water supplies for Bingara and Gravesend and environmental releases for the Lower Gwydir wetlands are supplied from Copeton Dam, the major storage in the valley. Most irrigation diversions occur below Pallamallawa, facilitated by a network of weirs and regulators on the Gwydir River and its effluents.

The Gwydir catchment is within the traditional lands of the Gomeroi/Kamilaroi people. There are now over 26,000 people living within the catchment. The largest town is Moree (8,000 people), which is the main commercial centre for the surrounding agricultural areas. It is also a major transport and tourism hub, being located at the junction of the Gwydir and Newell highways. There are a number of smaller towns of 1,000 to 2,000 people—Uralla and Guyra in the New England tablelands, and Bingara and Warialda in the middle of the catchment. Smaller villages include Bundarra, Delungra, Pallamallawa and Tingha, which have populations of 300 to 700 people.

Accounting extent

The accounting extent for surface water is illustrated in Figure 1. The accounted river extent is the Gwydir River from downstream of Copeton Dam to Millewa, the Mehi River from its initial effluent with the Gwydir River to near Collarenebri, Mallowa Creek, Moomin Creek, Carole Creek and Gil Gil Creek from its junction with Carole Creek to Gil Gil Creek at Galloway. Note that the accounted component of Gil Gil Creek extends beyond the surface water catchment boundary of the Gwydir and into the Border Rivers catchment, as orders in this section are met using resources from the Gwydir.

All licences managed under the *Water Sharing Plan for the Gwydir Regulated River Water Source* are considered. While physical groundwater volumes that interact with the regulated river are included in GPWAR statements where possible (and any interactions not directly estimated form part of the unaccounted difference) all other groundwater flows and groundwater management are excluded from the GPWAR.

The GPWAR includes estimates for end of system flows. These are the volumes at the end of the regulated water source and is not an estimate of the total volume that would enter the Barwon River.

The Gingham Channel, Mallowa Creek, Lower Gwydir River, Ballinboora Creek, and Thalaba Creek receive domestic and stock replenishment flows from the Gwydir Regulated River Water Source but do not themselves form part of this water source.





Figure 1: Surface water geographical extent of the accounts

Snapshot

The key indicators for 2020-21 relative to historical information are presented in Figure 2. For the reporting period, rainfall was very high while major storage inflow, account usage, effective allocation (carryover plus allocation) and temporary trading activity were all high.

Figure 2: 2020-21summary indicators



Climate

At Pallamallawa (central catchment), 840 mm of rainfall was recorded in the reporting period (Table 1). Comparatively this volume of rainfall is:

- 141% of the long-term historical median rainfall for this location
- 74% of the highest volume on record at the location.

The majority of rainfall fell in January 2021 (127 mm) and March 2021 (243 mm) (Figure 3 and Figure 4).

At Collarenebri (lower catchment), 617 mm of rainfall was recorded in the reporting period (Table 2). Comparatively this volume of rainfall is:

- 132% of the long-term historical median rainfall for this location
- 55% of the highest volume on record at the location.

The majority of rainfall fell March 2021 (160 mm) and December 2020 (89 mm) (Figure 3 and Figure 4).

Spatially, it was extremely wet relative to average conditions across the majority of the catchment with the exception of the far western area which experienced average conditions (Figure 5 and Figure 6).

Figure 3: Monthly rainfall at Collarenebri and Pallamallawa for the reporting period against historical median




Figure 4: Monthly rainfall deviation of the reporting period compared to historical median




Table 1: Monthly rainfall statistics at Pallamallawa (mm)¹

Month	Jul	Aug	Sep	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Annual
2020-21	14.4	43.2	12.0	48.6	2.4	121.2	127.0	84.6	243.2	29.6	34.4	79.8	840.4
Historical Mean	42.7	33.2	33.7	50.6	64.6	69.1	81.2	73.3	55.1	34.3	39.0	38.0	613.3
Historical Median	35.2	28.1	24.6	48.2	54.4	58.0	65.6	53.6	39.6	24.1	27.2	30.0	596.3
Historical Lowest	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	303.9
Highest	250.8	159.7	182.2	210.3	271.0	256.9	323.9	320.9	250.4	203.6	176.8	203.8	1128.2
Highest year	1949-50	1965-66	1969-70	1953-54	2010-11	1969-70	1945-46	1975-76	1981-82	1987-88	1912-13	2004-05	2011-12

Table 2: Monthly rainfall statistics at Collarenebri (mm)¹

Month	Jul	Aug	Sep	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Annual
2020–21	33.6	20.4	28.2	47.3	0.8	88.8	75.5	97.0	160.4	9.8	29.0	26.3	617.1
Historical Mean	34.3	26.4	25.8	37.7	47.4	52.6	67.3	57.2	49.0	33.5	34.2	34.8	496.4
Historical Median	25.0	17.2	17.0	33.1	35.8	37.6	40.0	37.4	33.0	20.5	22.6	27.2	468.3
Historical Lowest	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	187.7
Historical Highest	159.7	135.0	157.3	167.1	241.2	216.4	508.4	351.4	254.2	356.0	216.2	148.1	1113.8
Highest year	1949-50	1917-18	1905-06	1933-34	1999-00	1990-91	1973-74	1975-76	1893-94	1989-90	1982-83	2004-05	1973-74

¹ Long term statistics are from the Bureau of Meteorology—climate data online, using the climatic stations '48031—Collarenebri (Albert St)' and '53033—Pallamallawa Post Office'. Historical record statistics commence in 1913 for Pallamallawa and 1885 Collarenebri.







Figure 6: Average annual rainfall in the Gwydir catchment (1961–90)



Dam inflows and volume

Inflows

Historically, the long-term average annual inflow² at the Copeton storage site has varied significantly, cycling through prolonged periods of wet and dry flow regimes. Broadly, the data (Figure 7) illustrates predominately:

- dry conditions from 1900 to 1950
- wet conditions from 1950 to 1980
- dry conditions from 1980 to present.

For the reporting period, inflow to Copeton dam (Figure 8) was 578,555 megalitres, which is:

- 145% of the long-term average annual inflow (401,131 megalitres per year)
- High relative to the historical record, exceeding 78% of years on record (1890–91 to 2020– 21)

The highest inflows in the reporting period occurred in March 2021, where a maximum daily mean inflow of 114,412 megalitres per day was reached (Figure 9).




Figure 7: Long-term annual flow upstream of Copeton Dam cumulative deviation from mean

² Inflows are back-calculated storage inflow for period from storage construction and gauged or rainfall runoff model for the prior period





Figure 8: Long-term inflows to Copeton Dam against mean and reporting year inflow





Storage volume

Copeton Dam is the main supply storage in the regulated Gwydir system. The storage was completed in 1972 and has a full supply capacity of 1,361,720 megalitres. During the reporting period the:

- volume held in storage commenced at 198,106 megalitres or 15% of full supply capacity (Figure 10)
- volume held in storage at the end of the reporting period was 665,295 or 49% of full supply capacity, an increase of 34% for the year
- maximum volume held during the reporting period was 665,295 or 49% of full supply capacity on 30 June 2021.




Figure 10: Copeton Dam volume and percentage of full supply volume 2020-21

Major flow events

- There was one major flow events in the Gwydir River during 2020–21. With remaining instream volumes associated with regulated releases from Copeton storage.
- The maximum daily flow rate at Pallamallawa was 154,110 megalitres per day and occurred on 24 March 2021 (Figure 11).
- River height exceeded the major flood level indicator (assessed at the Yarraman Bridge gauging station) once during the reporting period (Figure 12). Height remained below 4 metres for the rest of the reporting period which is below the minor flood level.





Figure 11: Gwydir flow events for reporting period





Surface water resources and management

Legislation

The water source was managed under rules and requirements set out in the *Water Sharing Plan* for the Gwydir Regulated River Water Source 2016. This water sharing plan started on 1 July 2016 and will remain active until 30 June 2026 or until a replacement plan is gazetted. The water sharing plan was produced to meet the water management principles outlined in the NSW *Water Management Act 2000*.

Access rights

Excluding basic landholder rights (see Note 17), the right to a share of the water supply is controlled through the issue and management of water access licences.

- Access licence share components remained unchanged in the reporting period except for Domestic and Stock (Domestic), which increased from 88 to 388 shares (Figure 13).
- Total issued share component on 30 June 2021 was 718,282 including 181,398 of supplementary shares.




Figure 13: Total issued share component, including held environmental water

Table 3: Issued share component on 30 June 2021

Category	Issued share component
Domestic and Stock	2,506
Domestic and Stock [Domestic]	388
Domestic and Stock [Stock]	230
Local Water Utility	3,836
General Security	509,665
High Security	20,200
High Security (Research)	60
Supplementary Water	181,398
Total	718,282

Allocation account summary

A summary illustration of the accounting for High Security and General Security access licence categories in the Gwydir Regulated River is provide in Figure 14 and Figure 15 respectively. Detailed information on the water accounts for all categories of licence issued are provided in Note 1 of this report.





Figure 14: Annual water account summary Gwydir Regulated River High Security





Access licence account management

A continuous accounting model is adopted for general security holders that allows these licences to hold (and carryover) over up to 1.5 megalitres per issued share. There is no maximum AWD and water will be continually shared as resource becomes available. The total annual account usage plus assignments out cannot exceed more than 3 megalitres per issued share plus assignments in. Additionally, the 3-year rolling usage plus allocations assignments out in those 3 years cannot exceed 3 megalitres per issued share plus the volume of assignments in.

All other categories have an account limit of 100% per megalitre per share and cannot carryover water between water years. The access licence accounting rules are summarised in Table 4.

Table 4: Gwydir licensed allocation accounting rules

Licence category	Account limit	Carryover limit	Annual use limit	3-year use limit	Maximum AWD
Domestic and Stock	100%	0%	N/A	N/A	100%
Domestic and Stock [Domestic]	100%	0%	N/A	N/A	100%
Domestic and Stock [Stock]	100%	0%	N/A	N/A	100%
Local Water Utility	100%	0%	N/A	N/A	100%
Regulated River (General Security)	1.5 ML/Share	1.5 ML/Share	3 ML/Share ³	3 ML/Share ³	N/A
Regulated River (High Security)	1 ML/Share	0 ML/Share	N/A	N/A	1 ML/Share
Regulated River (High Security) (Research)	1 ML/Share	0 ML/Share	N/A	N/A	1 ML/Share
Supplementary	N/A	0 ML/Share	N/A	N/A	1.25 ML/Share ⁴

Extreme events stage and temporary water restrictions

The NSW Extreme Events Policy was released in October 2018 to provide a framework for managing extreme events in the major river systems of the NSW Murray-Darling Basin. This framework is based on a staged approach, providing a range of measures for water managers to implement as conditions deteriorate. Conditions improved throughout the 20/21 water year. Most valleys were rated in Stage 1 normal operations by January 2021 and all valleys by April 2021.

Temporary water restrictions can be implemented to manage a water shortage. These restrictions issued under section 324 of the Water Management Act 2000 were imposed in several river valleys in 2019/20 to preserve water for critical needs.

Table 5 outlines the conditions that may be associated with different stages of criticality for surface water quality. Further information is available at industry.nsw.gov.au/water/what-we-do/legislation-policies/eep

Table 5: Determination of stages of criticality for surface water quality

Stage	Stage description	Stage evidence base
1	Normal management	Can deliver all account water under normal river operations practices.
2	Emerging drought ⁵	Unable to deliver 100% of high priority account water and maximum expected use of general security under normal river operations practices.
3	Severe drought	Only able to deliver restricted high priority demands and restricted remaining general security account water.
4	Critical drought	Only able to deliver restricted town water supply, stock and domestic and other restricted high priority demands.

³ The annual and 3-year use limit for general security is assessed including allocation assignments (temporary trading), whereby usage plus trade out are compared to the relative limit plus allocation assignments in

⁴ 2016–17, 2017–18, 2018–19 only and then reverts to 1 megalitre per share

⁵ Valleys may be declared in Stage 2 Recovering after good inflows when conditions are improving but are not yet back to normal operations.

Broad-scale northern Basin restrictions

Gwydir temporary water restrictions

There were no temporary water restrictions during the reporting period.

Extreme events stage

At the commencement of the reporting period:

- The Stage of Criticality for surface water quality in the Gwydir River valley was rated as Stage 2 (Recovering).
- Copeton Dam was at 15% of capacity.
- All licence classes except General Security received an AWD of 100% or equivalent 1 ML/Share.
- General Security received an AWD of 0% or equivalent 0 ML/Share.

During the reporting period:

- General security allocation was increased by 0.017 ML/share in August 2020 with further increases occurring in September, October, January, February, April, May and June.
- Significant inflows during January 2021 and improved storage levels resulted in Stage of criticality for surface water quality moving from Stage 2 to Stage 1 (normal operation).
- Although only small allocation announcements were made for general security licences during the first half of the reporting period, by June 2021 cumulative allocation announcements had reached 0.58 ML/Share.

At the End of the Reporting Period

- Copeton Dam was at 49% of capacity
- Gwydir River valley was rated as Stage 1 (Normal management)

Drought measures

 Block releases were initially used for the delivery of general security orders in December 2020, but by January 2021 the system had returned to normal on-demand deliveries.





Figure 16: Drought stage for the reporting period referenced with monthly headwater storage inflows, monthly storage inflow variance from mean and storage percent full.

Water availability

- Domestic and Stock, Local Water Utility and High Security access licences (including subcategories) received an opening available water determination (AWD) of 100%, the maximum allowable under the water sharing plan.
- Supplementary access licences received an opening AWD of 1.0 megalitres per share.
 Each year of the plan this licence category has been granted an available water determination of 1 megalitre per share, however, access to this water is contingent on high-flow events being available.
- At the water source level 105 days of supplementary access was available in the reporting period. Historical and reporting period supplementary access periods are illustrated in Figure 19.
- General Security access licences had a carryover of 27,565 megalitres into the reporting period, equating to 5.4% of total issued general security share.
- General Security access licences received an opening AWD of 0 megalitres per share.
- Additional announcements were made for General Security in August (0.017 ML/share), September (0.0307), October (0.003), January (0.0711), February (0.035), April (0.3912), May (0.023) and June (0.009).
- The total General Security AWD for the reporting period was 0.58 megalitres per share, taking the total water availability (carryover plus AWD volumes) to 63.4% of issued share component. Incremental carryover and announcements for the reporting period and historical years under water sharing plan management is provided in Figure 17.

- Water availability^{[6][7][8]} for regulated supply categories of licence (excludes supplementary) was up significantly relative to the prior reporting period (Figure 18) and was well above the average under water sharing plan management conditions (2004-05 to 2020–21).
- By volume 69% of the 587,866 megalitres of tributary inflows to the Gwydir River downstream of Copeton dam was contributed by the Horton River (Figure 19).

Figure 17: Incremental available water determination and carryover volumes for 'General Security' as a proportion of share component



⁶ Supplementary licences have been excluded. Each year of the plan this licence category is granted an available water determination of 100%, however access to this water is contingent on high flow events available. Actual usage information against this category of licence is available in Note 1 and Note 18 of this GPWAR.

⁷ At the commencement of the water sharing plan (2004-05) water held in general security accounts was allowed to be brought forward as an opening balance.

⁸ Includes all access licences issued under the water sharing plan and therefore held environmental water.

Domestic and Stock ■ General Security High Security Local Water Utility 180 Water Availability (% of Entitlement) 160 140 120 100 80 60 40

2012-13

2014-15

2016-17

2018-19

2020-21

Figure 18: Gwydir account water availability (carryover plus AWDs)




2006-07

2008-09

2010-11

20

2004-05






Figure 20: Measured tributary inflow contributions

Account usage

Account usage refers to the total volume of water debited against an access licence.

- Account usage from the regulated supply totalled 57,185 megalitres for the reporting period which was an increase from the previous reporting period but is well below average usage under water sharing plan management conditions (Figure 21).
- Additionally, 145,248 megalitres was accessed from high-flow supplementary events.
- Average usage excluding supplementary access decreased to 131,906 megalitres (2004– 05 to 2020–21)
- Average Usage including supplementary access increased to 194,365.
- Refer to disclosure Note 3 for further usage details.




Figure 21: Access licence account usage

Utilisation and inactive share

We consider an access licence entitlement inactive if the holding does not use water or access the temporary trade market for the reporting period. Utilisation reflects the amount of water used from regulated supplies (excludes supplementary water), relative to the maximum amount available for use in the water year.

For the reporting period:

- 14% of general security share component was inactive for the reporting period (75,506 unit shares), down from 53% in the prior reporting period (Table 6)
- no high security share component was inactive which is consistent with the prior reporting period
- a total of 1,428 shares of domestic and stock (and subcategories) were inactive (57% of issued share)
- 3% of supplementary share component was inactive for the reporting period, down from 6% in the prior reporting period, where there was no usage but trade activity
- utilisation of available water from regulated supplies (excludes 'Supplementary') decreased to 16% from 41% in the previous year (Figure 22).

⁹ Differs from previously reported value due to updated information




Figure 22: Gwydir account utilisation

Table 6: Gwydir inactive licence summary for the reporting period

Licence category	Inactive licences (number)	Inactive share component	Inactive share % of total	Inactive share % of total prior year (2019–20)
Domestic and Stock	43	1428	57%	55%
Domestic and Stock [Domestic]	5	388	100%	100%
Domestic and Stock [Stock]	17	130	57%	80%
Local Water Utility	0	0	0%	2%
Regulated River (General Security)	91	73489	14%	53%
Regulated River (High Security)	5	11	0%	0%
Regulated River (High Security) [Research]	1	60	100%	100%
Total regulated supply	162	75,506	16%	51%
Supplementary Water	51	5,097	3%	6%

Temporary trading (allocation assignments)

Temporary trading is implemented in this water source under the section 71T (assignment of water allocations between access licences) of the *Water Management Act 2000*.

The total volume transferred under allocation assignments (75,046 megalitres) in the reporting period was 59% higher than the prior reporting period and was the fifth highest under water sharing plan management conditions (2004–05 to 2020–21) (Figure 23).




Figure 23: Allocation assignment total volumes

Commercial temporary trading statistics

- A total of 17 assignment was processed for commercial consideration, transferring 7,216 megalitres of water between holder accounts.¹⁰
- The average price in the reporting period was \$325 per megalitre (\$323 volume weighted), which was the third highest since operation under water sharing plan management conditions (Figure 24).
- Total trade value for the reporting period (\$2,330,996) was significantly higher than the prior reporting period reflecting the higher quantities being traded with increasing resources.
- Further details on allocation assignments for the reporting period are available in Note 4 of this GPWAR.

¹⁰ Trades were tagged as commercial if the consideration per megalitre exceeded \$1. A maximum limit was also applied to eliminate outliers from the dataset.




Figure 24: Allocation assignments commercial statistics

Permanent trading (assignment of share and transfer of licence)

Permanent trading is implemented in this water source under the sections 71 M (Transfer of access licences) and 71Q (Assignment of rights under access licence) of the *Water Management Act 2000*.

- The permanent trading market remains relatively inactive.
- During the reporting period:
 - 1 general security share assignment (71Q) was processed, with a weighted average price of \$3,782 per share (Figure 25)
 - o zero commercial share assignments occurred for other categories of access licence.
- The general security sale price within the Gwydir relative to other NSW regulated river water sources selling share in the reporting period is provided in Figure 26.
- No commercial exchange of high security share occurred via share assignment transactions.
- No environmental share assignments have occurred since 2010–11 (Figure 27).
- An additional 13,162 shares were exchanged for monetary consideration (greater than \$1 per share) through change of holder licence dealings (Figure 28).





Figure 25: Share assignment price statistics for General Security









Figure 27: Share assignment trades for environmental and non-environmental licence holders





Replenishment flows


Replenishment flow requirements of the water sharing plan are detailed in Note 15 of this GPWAR. There were no replenishment flows delivered from storage within the reporting period. Thalaba Creek replenishment flow under clause 58(1)(b) of the Water sharing plan was planned as part of scheduled block releases in December 2020 however, good tributary inflows meant this was not required.

Held environmental water

Held environmental water refers to access licences that are managed for the purpose of sustaining and improving environmental outcomes within the system.

- There was no change to held environmental water holdings for the reporting period (Figure 31).
- 135,965 shares were held by environmental managers as of 30 June 2021.
- Held environmental usage totalled 8,604 megalitres from the regulated supply (excluding supplementary access (Figure 29). Additionally, there was 9,412 megalitres of environmental usage associated with supplementary licence holdings.
- Utilisation of available account water was 11% for the regulated supply (Figure 30).
- Details on held environmental accounting for the reporting period are available in Note 5 of this GPWAR.

Figure 29: Held environmental account usage






Figure 30: Held environmental account utilisation

Planned environmental water—environmental contingency allowance

Planned environmental water refers to a range of environmental allowances and provisions implemented under the water sharing plan to improve environmental outcomes.

- The environmental contingency allowance (ECA) had an opening balance of 19,272 megalitres.
- 31,130 megalitres was credited to the ECA for the reporting period
- The resulting ECA Availability being 50,402 megalitres.
- 7,978 megalitres of ECA was delivered (Figure 32).
- The ECA had a closing balance of 42,424 megalitres.
- Further details are available in Note 6 of this GPWAR.

Planned environmental water—other

- All minimum flow targets were considered met for the reporting period.
- 323,184 megalitres of supplementary access events was reserved for environmental benefits.
- Further details are available in Note 6 of this GPWAR.

Figure 31: Held environmental water share component in the Gwydir





Figure 32: Environmental contingency allowance summary



Water accounting statements

Significant water accounting policies

We have used an accrual basis of accounting to prepare the water accounting statements in this GPWAR. All figures are in megalitres (ML).

We have excluded the 'Statement of Physical Flows' from this GPWAR as all transactions have been presented in the statements 'Water Assets and Liabilities' and 'Changes in Water Assets and Water Liabilities'. We have included a physical flow diagram that represents the physical movements of water to more clearly depict those accounting processes associated with physical flow movement.

For general information on how to interpret the NSW Department of Planning and Environment water accounting statements, refer to the *Guide to General Purpose Water Accounting Reports* available for download from the Lands and Water website (www.industry.nsw.gov.au/water).

Quantification of data

Data accuracy


The data used to account for water movement and management in the reporting entity has been obtained from a variety of sources and systems. The data ranges from observed values where we anticipate high accuracy through to modelled results and estimates where accuracy can be highly variable, depending on a range of factors. To improve accuracy and prevent misuse of the data in the accounts, we have added an accuracy assessment to all figures in the water accounting statements (Table 7).

Table 7: Water account data accuracy estimates key

Accuracy	Description
A1 ¹¹	± 0% Data is determined rather than estimated or measured. Therefore, the number contains no inaccuracies.
A	± 10%
В	± 25%
С	± 50%
D	± 100%

¹¹ Non-physical administration items, such as available water determinations, trading and carryover volumes are assumed to have no inherent error for the purposes of this report. Items are reported as extracted from the NSW Department of Planning and Environment corporate database.

2020-21 Gwydir physical flows mass balance diagram



Statement of water assets and water liabilities

For the year ended 30 June 2021

In all tables (..) denotes a negative value.

Some figures may differ from previous general purpose water accounting statements where updated information has been provided after the reports was published.

Surface water assets

1.Surface water storage	Accuracy	Notes	30-06-2021	30-06-2020
Copeton Dam	Α	7	665,295	198,106
River	В	8	17,012	1,070
Total surface water storage (Asws)	-	-	682,307	199,176
Change in physical surface water storage	-	-	483,131	58,083

Surface water liabilities

2.Allocation account balance	Accuracy	Notes	30-06-2021	30-06-2020
Domestic and Stock	A1	1	0	(22)
High Security (HS)	A1	1	(2)	(0)
Local Water Utility	A1	1	(5)	(14)
General Security	A1	1	288,961	27,565
Total allocation account balance (Lsws)	-	-	288,954	27,529
Change in allocation account balance	-	-	261,425	14,158

3. Environmental contingency allowance (ECA) Balance	Accuracy	Notes	30-06-2021	30-06-2020
ECA	A1	6	42,424	19,272
Total ECA Balance (ECA)	-	-	42,424	19,272
Change in ECA balance	-	-	23,152	(4,058)

Surface water net changes

4. Net changes	Accuracy	Notes	30-06-2021	30-06-2020
Net surface water assets (Asws – Lsws – ECA)	-	-	350,929	152,375
Change in net surface water assets	-	-	190,554	47,983

Changes in water assets and water liabilities

For the year ended 30 June 2021 (1 of 3)

1. Changes in surface water storage (physical water balance)

Surface water storage increases	Accuracy	Notes	2020-2021	2019-2020
Copeton Dam	-	-	-	-
Inflow	А	9	578,555	113,652
Rainfall	В	10	18,004	5,624
River	-	-	-	-
Rainfall	С	11	19,254	21,978
Inflow from Copeton releases	А	14	106,060	45,464
Tributary inflow	-	-	-	-
Gauged tributaries	А	12	587,328	53,494
Ungauged runoff estimate	С	13	233,000	67,000
Total surface water storage increases (Isws)	-	-	1,542,201	307,211

Surface water storage decreases	Accuracy	Notes	2020-2021	2019-2020
Copeton	-	-	-	-
Storage release	A	14	106,060	45,464
Evaporation	В	10	23,310	15,394
River	-	-	-	-
Evaporation	С	11	26,318	49,065
End-of-system flow: Other	А	15	268,553	67,932
End-of-system flow: Replenishment	А	15	0	180
End-of-system flow: Flow to wetlands	А	15	298,552	31,405
Net river outflow to aquifer	D	20	18,900	17,950
Extractions	-	-	-	-
Basic rights extractions	С	17	6,000	6,000
Other river extractions	А	16	202,432	8,378
Total surface water storage decreases (Dsws)	-	-	950,125	241,768
Unaccounted volume (balancing Item) (Usws)	A1	19	108,945	7,287

Net surface water storage changes	Accuracy	Notes	2020-2021	2019-2020
Net surface water storage inflow (Isws-Dsws-Usws)	-	-	483,131	58,156

Changes in water assets and water liabilities

For the year ended 30 June 2021 (2 of 3)

2. Changes in allocation accounts

Allocation account increases	Accuracy	Notes	2020-2021	2019-2020
Available water determinations	-	-	-	-
Domestic and Stock	A1	2	2,997	2,824
General Security	A1	2	295,526	11,058
High Security	A1	2	20,200	20,200
High Security (Research)	A1	2	60	60
Local Water Utility	A1	2	3,836	3,836
Internal trade—buyers	A1	4	30,817	24,494
Supplementary demand	Α	18	145,248	19,559
Total allocation account increases (laa)	-	-	498,684	82,030

Allocation account decreases	Accuracy	Notes	2020-2021	2019-2020
Account usage	-	-	-	-
Domestic and Stock	А	3	1,007	787
General Security	Α	3	45,050	6,382
High Security	Α	3	8,591	10,615
Local Water Utility	А	3	2,537	2,440
Supplementary	А	3	145,248	19,559
Account forfeiture	-	-	-	-
Domestic and Stock	A1	1	1,944	1,832
General Security	A1	1	0	0
High Security	A1	1	13	73
High Security (Research)	A1	1	60	60
Local Water Utility	A1	1	1,304	1,410
Over order	-	-	-	-
Domestic and Stock	A1	21	24	211
General Security	A1	21	624	1
High Security	A1	21	42	8
Internal trade—sellers	A1	4	30,816	24,494
Account balance adjustment	A1	22	0	0
Total allocation account decreases (Daa)	-	-	237,260	67,872

Net change in allocation accounts	Accuracy	Notes	2020-2021	2019-2020
Net allocation account balance increase (laa – Daa)	-	-	261,424	14,158

Changes in water assets and water liabilities

For the year ended 30 June 2021 (3 of 3)

3. Change in environmental contingency allowance (ECA)

ECA account increases	Accuracy	Notes	2020-2021	2019-2020
Account increase due to General Security AWD	A1	6	31,130	1,170
Total ECA increase (leca)	-	-	31,130	1,170

ECA account decreases	Accuracy	Notes	2020-2021	2019-2020
Account usage	А	6	7,978	5,228
Account balance—adjustment (ECA decrease)	-	-	0	0
Total ECA decrease (Deca)	-	-	7,978	5,228

Net environmental provisions changes	Accuracy	Notes	2020-2021	2019-2020
Net environmental contingency allowance increase (leca – Deca)	-	-	23,152	(4,058)

4. Overall changes

Surface water assets	Accuracy	Notes	2020-2021	2019-2020
Change in net surface water assets (Isws-Dsws-	_	_	198.555	48.056
Usws-laa+Daa-leca+Deca)			130,333	40,030

Note disclosures

Reconciliation and future prospect descriptions

Reconciliation of change in net water asset to net change in physical water storage ¹²	2020–21 ML	2019–20 ML
Change in net surface water assets	198,554	47,983
Non-physical adjustments	-	-
Net change in allocation accounts	261,425	14,158
Net change in claims to water: ECA	23,152	(4,058)
Net change in physical surface water storage	483,131	58,083

Reconciliation of closing water storage to total surface water assets	30 June 2021	30 June 2020	
Closing water storage	-	-	
Surface water storage	682,307	199,176	
Additional surface water assets	N/A	N/A	
Total surface water assets	682,307	199,176	

Water assets available to settle water liabilities and future commitments within 12 months of reporting date

Datasets to produce an informative 12-month forecast for report users are generally not available at the time of writing.

In lieu of this, the web links to below provide the latest water availability information, allocations and usages for the Gwydir Regulated River Water Source.


Carryovers and available water determinations for the 2020–21 are provided as at the time of writing (Table 8) along with information about the Gwydir system's reliability produced from the NSW industry long term planning models (Figure 33 and Figure 34).

¹² All figures can be derived from or found directly in the Water Accounting Statements of the General Purpose Water Accounting Report. All figures are in megalitres.

Latest water availability

You can find the latest information on water availability, including water allocation statements, water allocations summaries and 2020-21 available water determinations, on the NSW Department of Planning and Environment webpage at industry.nsw.gov.au/water/allocations-availability/allocations

You can also subscribe to receive the latest updates.



Latest storage volumes

See real-time information on current storage volumes at realtimedata.waternsw.com.au

Latest usage data

Usage for the open water year (updated weekly), and historical usage is available to view and download via the NSW Industry usage dashboard at industry.nsw.gov.au/water/allocations-availability/water-accounting/usage-dashboard

Significant events since reporting period

System inflows have continued to track above historical averages since the end of the reporting period. At the time of writing (May 2022) Copeton storage volume was at 95.5% of full supply capacity (rising trend).

System reliability¹³

The latest long-term planning model (IQQM) reflecting a water sharing plan management scenario in the Gwydir provides indicative system reliability information for the start and end of a watering season¹⁴.

In any given year, the simulation indicates High Security entitlements are likely to a have full allocation 100% of the time.

At the start of the water year, the simulation indicates that General Security licence holders receive an equivalent allocation of 100% or greater 28% of the time (Figure 33). Availabilities significantly increase throughout the water year when usages have started and the storage is supplemented from new inflow. By the end of the water year, the simulation results indicate a water availability of 100% or greater, 46% of the time (Figure 34).






Figure 33: Start of water year simulated availability for General Security access licences



¹³ Models used by state water agencies are subject to continuous improvements and updates. The reliability described in this report represents the information available when the report was compiled and may vary from reliability computed in the latest version of the models.

¹⁴ Modelled data simulated as July to June water year. Simulation period 1 June 1892 to 30 June 2016.

Figure 34: End of water year simulated availability for General Security access licences



Carryovers and available water determinations 2020–21

Table 8: Gwydir carryovers and available water determinations 2020–21 (as of December 2020)

Date	Individual announcement	Share component	Allocation volume (ML)	Cumulative volume (ML)	Allocation volume (%)	Cumulative volume (%)	Balance available (ML)	Balance not available (ML)	Balance total (ML)	Balance available (%)	Balance total (%)
Domestic and Stock											
1-Jul-20	Opening	2,506	-	-	0.0%	0.0%	(21)	0	(21)	(0.8)%	(0.8)%
1-Jul-20	AWD 100.0 %	2,506	2,506	2,506	100.0%	100.0%	2,485	0	2,485	99.2%	99.2%
Domestic and Stock[Domestic]											
1-Jul-20	Opening	88	-	-	0.0%	0.0%	0	0	0	0.0%	0.0%
1-Jul-20	AWD 100.0 %	88	88	88	100.0%	100.0%	88	0	88	100.0%	100.0%
Domestic ar	nd Stock[Stock]										
1-Jul-20	Opening	230	-	-	0.0%	0.0%	(1)	0	(1)	(0.3)%	(0.3)%
1-Jul-20	AWD 100.0 %	230	230	230	100.0%	100.0%	229	0	229	99.7%	99.7%
Local Water	Utility										
1-Jul-20	Opening	3,836	-	-	0.0%	0.0%	(14)	0	(14)	(0.4)%	(0.4)%
1-Jul-20	AWD 100.0 %	3,836	3,836	3,836	100.0%	100.0%	3,822	0	3,822	99.6%	99.6%
Regulated F	River (General Security)										
1-Jul-20	Opening	509,665	-	-	0.0%	0.0%	27,565	0	27,565	5.4%	5.4%
1-Jul-20	AWD 0.0 ML/share	509,665	0	0	0.0%	0.0%	27,565	0	27,565	5.4%	5.4%
7-Aug-20	AWD 0.017 ML per Share	509,665	8,662	8,662	1.7%	1.7%	36,227	0	36,227	7.1%	7.1%
7-Sep-20	AWD 0.0307 ML per Share	509,665	15,645	24,306	3.1%	4.8%	51,871	0	51,871	10.2%	10.2%
8-Oct-20	AWD 0.003 ML per Share	509,665	1,529	25,835	0.3%	5.1%	53,400	0	53,400	10.5%	10.5%
Regulated F	River (High Security)										
1-Jul-20	Opening	20,200	-	-	0.0%	0.0%	0	0	0	0.0%	0.0%
1-Jul-20	AWD 1.0 ML per Share	20,200	20,200	20,200	100.0%	100.0%	20,200	0	20,200	100.0%	100.0%
Regulated F	River (High Security)[Research]										
1-Jul-20	Opening	60	-	-	0.0%	0.0%	0	0	0	0.0%	0.0%
1-Jul-20	AWD 100.0 %	60	60	60	100.0%	100.0%	60	0	60	100.0%	100.0%
Supplement	ary Water										
1-Jul-20	Opening	181,398	-	-	0.0%	0.0%	0	0	0	0.0%	0.0%
1-Jul-20	AWD 1.0 ML per Share	181,398	181,398	181,398	100.0%	100.0%	181,398	0	181,398	100.0%	100.0%

Note 1—Allocation accounts

This note is a reference for the volume held in the allocation accounts at the time of reporting and is also relevant for the various processes that either increase or decrease an allocation account throughout the water year.

The volume of water that is in the licence allocation accounts at the time of reporting is a net balance for the relevant licence category. It represents that volume of water that can be carried forward to the next water year as dictated by the carryover rules in place for that year or required under the water sharing plan.

A negative number for the carryover figure indicates that more usage has occurred than has been allocated to the account, and the deficit must be carried forward to the next season.

Water that is in the accounts at the end of a water year but is not permitted to be carried over is forfeited and has been represented as a decrease in water liability.

The accounting presented is relevant to licence category and is therefore inclusive of licences held by environmental holders (these are also detailed separately in Note 5).

Data type

Derived from measured data

Policy

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

Available on the NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water

Data accuracy

A1—Nil inaccuracy ±0%

Providing agency

NSW Department of Planning and Environment

Data source

WaterNSW/NSW Department of Planning and Environment—Water Accounting System (joint ownership)

Methodology

The carryover volume of water in the allocation account for each licence category is determined once all transactions and end-of-year forfeit rules have been applied. Below is list of typical transactions that can apply to an allocation account:

- available water determination (AWD) (detailed in Note 2)
- allocation account usage (detailed in Note 3)
- over-order debits
- forfeiture due to:
 - o no carryover being permitted (end-of-year forfeit)
 - allocation account limits
- licence conversion
- trade of allocation water between accounts (detailed in Note 4)
- · carryover rules.

Additional information

Table 10 summarises the water allocation accounts for each category of access licence. Table 9 describes each of the table components. All figures are in megalitres.

Table 9: Explanatory information for allocation account summary

Heading		Description					
Share		This is the total volume of entitlement in the specific licence category.					
Opening balance	•	The volume of water that has been carried forward from the previous year's allocation account					
AWD—available water determination		The total annual volume of water added to the allocation account as a result of allocation assessments. This figure includes additional AWD made as a result of a storage spill reset as defined in the water sharing plan.					
Licences	New	Increase in-account water as a result of issuing a new licence					
	Cancel	Decrease in account water as a result of a licence cancellation where account balance has not been traded to another licence					
Drought suspension	In	Temporary water restriction applied, reducing account water available for use in reported water year					
	Out	Temporary water restriction re-credit increasing account water available for use in reported water year					
Assignments	In	Increase in account water as a result of temporary trade in					
Out		Decrease in account water as a result of temporary trade out					
Account usage		Volume of water that is extracted or diverted from the river and is accountable against the access licence allocation					
Over-order debit		Volume of water ordered that exceeded the recorded usage for the corresponding periods. In licence categories where water order debiting applies, any orders in excess of usage are accountable against the licence.					
Forfeits	During year	Account water forfeited throughout the year as a result of the accounting rules specified in the water sharing plan. Forfeited water may occur due to account limits being reached, conversions between licence categories and various types of other licence dealings.					
	End-of-year forfeit	Account water that is forfeited at the end of the water year as a result of carryover rules that restrict the carry forward volume					
End-of-year balance	Available	Account balance that is available to be taken at the conclusion of the water year					
	Not available	That part of the remaining account balance that is not available to be taken at the conclusion of the water year. This is water in accounts that is in excess of the annual take limit.					
Carry forward		This represents the account water that is permitted to be carried forward into the next water year, as determined by the carryover rules.					

Table 10: Allocation account balance summary (reporting period)

Category	Share	Opening	AWD	Lic	ences		ought ension	Assign	ments	Account	Over order	During	End of year balance		End of	Carry
	Silare	balance	AVVD	New	Cancel	In	Out	In	Out	usage	debit	year forfeit	Available	Not Available	year forfeit	forward
Domestic and Stock	2,506	(21)	2,506	0	0	0	0	0	0	947	24	0	1,514	0	1,514	0
Domestic and Stock [Domestic]	388	0	261	0	0	0	0	0	0	0	0	0	261	0	261	0
Domestic and Stock [Stock]	230	(1)	230	0	0	0	0	0	0	60	0	0	169	0	169	0
Local Water Utility	3,836	(14)	3,836	0	0	0	0	13	0	2,537	0	0	1,299	0	1,304	(5)
General Security	509,665	27,565	295,526	0	0	0	0	30,804	19,260	45,050	624	0	288,961	0	0	288,961
High Security	20,200	(0)	20,200	0	0	0	0	0	11,556	8,591	42	0	11	0	13	(2)
High Security (Research)	60	0	60	0	0	0	0	0	0	0	0	0	60	0	60	0
Supplementary Water	181,398	0	181,398	0	0	0	0	44,229	44,229	145,248	0	0	36,150	0	36,156	(6)

Note 2—Available water determination (AWD) (allocation announcement)

This is the process by which the regulated surface water asset available for use within the regulated system is determined and shared. The process calculates the volume of water we add to an individual's licence allocation account. Announcements of allocations are made on a seasonal basis—usually corresponding with the financial year—and are updated on a regular basis or following significant inflow events. Under the *Water Management Act 2000* the announcements are termed available water determinations.

Data type

Derived from measured data

Policy

Water Management Act 2000 (NSW)

- o Chapter 3—Part 2 Access Licences.
- Clause 59—Available Water Determinations.

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

- o Part 8—Limits to the availability of water
- Division 1—Long-term extraction limit
- Division 2—Available water determinations.

Available on the NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water

Data accuracy

A1—Nil inaccuracy +/- 0%

Providing agency

NSW Department of Planning and Environment

Methodology

In the Gwydir Regulated Water Source, available water determinations (AWDs) are calculated based on a concept of continuous accounting that assesses the water contained in the headwater storages, periodically updating projections and distributing the stored resource available. All projections are for 2 years from the date of the assessment. Under continuous accounting, the AWDs are based on the actual volume of water in storage at the time of the resource assessment. This does not account for sequences of future inflows.

The process firstly involves assessing effective storage, which is the available storage volume after storage losses are accounted for. Storage losses cannot be controlled by a management rule, so they must be provided for first. After this, existing commitments are taken into account. Next, any uncommitted water is first committed to essential supplies. Then it is added to the delivery loss account to target a volume equivalent to a maximum of 30% of the deliverable General Security volume and then to the ECA account. Any remaining uncommitted water is then shared in proportion to the amount of entitlement in the remaining resource categories.

The essential supplies mentioned above consist of items such as:

- Stock and Domestic requirements
- Local Water Utilities (for example, town water supplies, industrial use)
- High Security (permanent plantings such as orchards and vineyards)
- end-of-system flow requirement resulting from the system operation
- minimum storage releases.

The volume of water distributed to licence categories is expressed as either a volume per share or as a percentage of share component, depending on the category of licence. The following table details each licence category and how it is announced.

Table 11: Access licence category announcement type

Licence category	AWD priority
General Security	Volume per share
High Security	Volume per share
Domestic and Stock ¹⁵	Per cent of share component
Local Water Utility	Percent of share component

The AWD for Supplementary licence accounts is a separate process and is not dependent on the water asset available. It is made once at the start of the year and unless there is a management change because of the growth in use strategy, it is maintained at the maximum value prescribed in the plan, which is generally 1 megalitre per share (equivalent to 100% of entitlement). Therefore, it is not considered to create a liability on the system and is only considered in terms of an extraction that reduces the water asset.

¹⁵ Domestic and Stock is further broken down into 3 sub-categories: Domestic and Stock, Domestic and Stock (Domestic) and Domestic and Stock (Stock). For the purposes of this report and the general-purpose water account they were all treated as Domestic and Stock.

Additional information

Table 13 summarises allocations for the reporting period. Table 12 describes each component presented in the summary.

Table 12: Allocation summary report notes

Heading	Description
Date	Date that available water determination was announced, and water was credited to accounts
Opening (ML)	Remaining allocation account balances at the conclusion of the previous season that is allowed to be carried forward to this season
Individual announcement	Actual available water determination announcement made to each licence category
Share component (entitlement)	Sum of the licensed volume of water within the licence category on the announcement date
Allocation volume (ML)	Volume of water credited to accounts within a licence category as a result of the announcement made
Cumulative volume (ML)	Cumulative total of the announced volumes for the water year and licence category
Allocation volume (%)	This is the announced volume expressed as a percentage of the share applicable on the particular date
Cumulative volume (%)	This is the cumulative volume expressed as a percentage of the entitlement applicable on the particular date
Balance available (ML)	Sum of water in allocation accounts that has been made available to be taken during the season
Balance not available (ML)	Water allocated that is not accessible at this point in time
Balance total (ML)	Sum of the total volume of account water in accounts
Balance available (%)	Balance available expressed as a percentage of the share component
Balance total (%)	Total account balance expressed as a percentage of the share component.

Table 13: Allocation announcements during the reporting period for Gwydir regulated river water source

Date	Individual announcement	Share component	Allocation volume (ML)	Cumulative volume (ML)	Allocation volume (%)	Cumulative volume (%)	Balance available (ML)	Balance not available (ML)	Balance total (ML)	Balance available (%)	Balance total (%)
Domestic a	and Stock										
1-Jul-20	Opening	2,506	-	-	0.0%	0.0%	(21)	0	(21)	(0.8)%	(0.8)%
1-Jul-20	AWD 100.0 %	2,506	2,506	2,506	100.0%	100.0%	2,485	0	2,485	99.2%	99.2%
Domestic and Stock [Domestic]											
1-Jul-20	Opening	88	-	-	0.0%	0.0%	0	0	0	0.0%	0.0%
1-Jul-20	AWD 100.0 %	88	88	88	100.0%	100.0%	88	0	88	100.0%	100.0%
2-Dec-20	Pro-rata AWD	388	173	261	44.6%	67.3%	261	0	261	67.3%	67.3%
Domestic a	and Stock [Stock]										
1-Jul-20	Opening	230	-	-	0.0%	0.0%	(1)	0	(1)	(0.3)%	(0.3)%
1-Jul-20	AWD 100.0 %	230	230	230	100.0%	100.0%	229	0	229	99.7%	99.7%
Local Wate	er Utility										
1-Jul-20	Opening	3,836	-	-	0.0%	0.0%	(14)	0	(14)	(0.4)%	(0.4)%
1-Jul-20	AWD 100.0 %	3,836	3,836	3,836	100.0%	100.0%	3,822	0	3,822	99.6%	99.6%
Regulated	River (General Security)										
1-Jul-20	Opening	509,665	-	-	0.0%	0.0%	27,565	0	27,565	5.4%	5.4%
1-Jul-20	AWD 0.0 ML/share	509,665	0	0	0.0%	0.0%	27,565	0	27,565	5.4%	5.4%
7-Aug-20	AWD 0.017 ML per Share	509,665	8,662	8,662	1.7%	1.7%	36,227	0	36,227	7.1%	7.1%
7-Sep-20	AWD 0.0307 ML per Share	509,665	15,645	24,307	3.1%	4.8%	51,871	0	51,871	10.2%	10.2%
8-Oct-20	AWD 0.003 ML per Share	509,665	1,529	25,836	0.3%	5.1%	53,400	0	53,400	10.5%	10.5%
15-Jan-21	AWD 0.0711 ML per Share	509,665	36,228	62,064	7.11%	12.2%	89,638	0	89,638	17.6%	17.6%
5-Feb-21	AWD 0.035 ML per Share	509,665	17,832	79,896	3.50%	15.7%	107,476	0	107,476	21.1%	21.6%
9-Apr-21	AWD 0.3912 ML per Share	509,665	199,328	279,224	39.12%	54.8%	306,856	0	306,856	60.2%	60.2%
7-May-21	AWD 0.023 ML per Share	509,665	11,716	290,940	2.30%	57.1%	318,579	0	318,579	62.5%	62.5%
7-Jun-21	AWD 0.009 ML per Share	509,665	4,586	295,526	0.90%	58.0%	323,164	0	323,164	63.4%	63.4%
Regulated	River (High Security)										
1-Jul-20	Opening	20,200	-	-	0.0%	0.0%	0	0	0	0.0%	0.0%
1-Jul-20	AWD 1.0 ML per Share	20,200	20,200	20,200	100.0%	100.0%	20,200	0	20,200	100.0%	100.0%
Regulated	River (High Security) [Research	h]									
1-Jul-20	Opening	60	-	-	0.0%	0.0%	0	0	0	0.0%	0.0%
1-Jul-20	AWD 100.0 %	60	60	60	100.0%	100.0%	60	0	60	100.0%	100.0%
Supplemen	ntary Water										
1-Jul-20	Opening	181,398	-	-	0.0%	0.0%	0	0	0	0.0%	0.0%
1-Jul-20	AWD 1.0 ML per Share	181,398	181,398	181,398	100.0%	100.0%	181,398	0	181,398	100.0%	100.0%

Note 3—Allocation account usage

This is the volume of water that is extracted, diverted or measured as usage and is accountable against an access licence. This figure excludes that water accounted as over- order debit, which is accounted for separately (see Note 21).

Data type

Measured/administration data

Policy

Not applicable

Data accuracy

A—Estimated in the range +/- 10%

Providing agency

NSW Department of Planning and Environment

Data source

WaterNSW/NSW Department of Planning and Environment—Water Accounting System (Joint ownership).

Methodology

Usage information is determined by either on-farm meters that measure extraction, gauges on diversion works or orders/releases when the volume cannot be effectively metered, such as an environmental watering event.

Meter readings are collected for individual licence holders at intervals during the year and converted via a calibration factor to a volume of water extracted. Water diverted from the river is measured by recording the height at either the gauge or weir, with the volume diverted being derived by passing these heights through a rating table. However, with multiple categories of access licences being extracted through the same pumps, more information and methodologies are needed to separate use under the various licence categories:

- based on periods of announcement—during periods of supplementary water announcements, extractions can be debited against the Supplementary water licences
- based on water orders—users place orders for water against an access licence and usages are debited against accounts in proportion to the orders placed
- licence category apportionment—if no water orders are available, water extracted is apportioned against categories of access licence in order of priority as set out in the next table. The ranking is based on the nature of and rules of each of the licence categories.

Table 14 shows the order in which extractions are apportioned to access licence categories, starting at priority 1. This is a generic list where not all categories will necessarily appear in this GPWAR. There are also various sub-categories of licence associated with some of these.

Table 14: Licence category metered usage apportionment table

Priority	Surface water
1	Supplementary
2	Uncontrolled Flow
3	Domestic and Stock
4	Regulated River High Security
5	Regulated River General Security
6	Conveyance
7	Local Water Utility
8	Major Water Utility

Additional information

Table 15 summarises account usage by licence category for the reporting period.

Table 15: Account usage summary

Licence category	Account usage (ML)
Domestic and Stock	947
Domestic and Stock [Domestic]	0
Domestic and Stock [Stock]	60
Local Water Utility	2,537
General Security	45,050
High Security	8,591
High Security (Research)	0
Supplementary	145,248
Total account Usage	202,432

Note 4—Internal trading (allocation assignments)

This represents the temporary trading (allocation assignments) of water between allocation accounts within the Gwydir Regulated River water source.

Data type

Administration

Policy

Water Management Act 2000

- Dealings with access licences (Division 4)
 - o 71T Assignment of water allocations between access licences

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

- Part 10 Access licence dealing rules
 - Available on the NSW Department of Planning and Environment website at <u>www.industry.nsw.gov.au/water</u>

Data accuracy

A1—Nil inaccuracy +/- 0%

Providing agency

NSW Department of Planning and Environment

Data source

WaterNSW/NSW Department of Planning and Environment—Water Accounting System (joint ownership)

Methodology

Trading is permitted between certain categories of access licences and between certain water sources. This is detailed in the water sharing plan or stipulated under the licence holder's conditions.

The net internal trade for each licence category is zero for a water year. As such, trades occur as both a water liability decrease (sellers of water) and a water liability increase (buyers of water).

Additional information

Table 16 presents the internal trading figures between licence categories. All figures represent a volume in megalitres.

Table 16: Gwydir allocation assignments summary

From	To General Security	To Local Water Utility	To Supplementary Water	Total
Local Water Utility	-	13	-	13
General Security	19,260	-	-	19,260
High Security	11,556	-	-	11,556
Supplementary Water	-	-	44,229	44,229
Total	30,804	13	44,229	75,033

Note 5—Held environmental water

This represents that environmental water that is held as part of a licensed volumetric entitlement. These licences are either purchased on the market by environmental agencies or issued as a result of water savings achieved through investment by those relevant agencies.

These licences are held within the same licence categories as all other water access licences and are subject to the same operating rules:

- available water determinations (AWD) for their share of the entitlement to be added to accounts
- carryover rules—the forfeiting of unused water that cannot be carried over
- provide water orders prior to use.

These licences are used to provide environmental benefit and outcomes to the catchment by either providing water to, or supplementing the water requirements of, specific environmental events or incidents.

Data type

Measured

Policy

• Water Sharing Plan for the Gwydir Regulated River Water Source 2016

Available on the NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water

Data accuracy

A—Estimated in the range +/- 10%

Providing agency

NSW Department of Planning and Environment

Data source

WaterNSW/NSW Department of Planning and Environment—Water Accounting System (Joint ownership)

Available Water Determination Register—NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water

Methodology

The water held for the environment represents a volume of water in corresponding allocation accounts. This allocation account represents the sum of the remaining volume of held environmental water at the conclusion of the water year once all transactions and forfeit rules have been applied to the accounts. These environmental balances are at the licence category level and represent the water that can be carried forward for use in the next year. Below is list of typical transactions that can apply to an environmental allocation account:

- AWD (including pro rata of AWD for new licences)
- licensed extractions
- forfeiture due to:
- carryover rules
- account spillage as a result of AWD

- licence conversions
- excess orders (where water order debiting is in place)
- licence conversion
- trade of allocation water between accounts.

In addition, the trade and purchase of environmental water is tracked to capture the movement of environmental entitlement both in number of entitlements, and volume.

Additional information

Table 18 summarises held environmental water for the reporting period. Table 17 explains the components. Table 19 summarises changes to the environmental portfolio since the previous reporting period. Table 20 provides environmental allocation movement through temporary allocation assignments.

Table 17: Explanatory information for environmental account summary

Heading		Description		
No. Licences		This is the number of environmental licences held.		
Category		Licence category issued under the water sharing plan		
Share		This is the total volume of entitlement in the specific licence category.		
Opening balance	е	The volume of water that has been carried forward from the previous year's allocation account		
AWD—available water determination		The total annual volume of water added to the allocation account as a result of allocation assessments		
Drought In suspension		Temporary water restriction applied, reducing account water available for use in reported water year		
Out		Temporary water restriction re-credit increasing account water available for use in reported water year		
Assignments In		Increase in account water as a result of temporary trade in		
	Out	Decrease in account water as a result of temporary trade out		
Account usage		Volume of water that is extracted or diverted or used and is accountable against the licence		
End-of-year balance	Available	Account balance that is available to be taken at the conclusion of the water year		
Not available		Account balance that is currently not available for use (e.g. restricted due to drought conditions or annual use limit restrictions)		
End-of-year forf	eit	Account water that is forfeited at the end of the water year as a result of carryover rules that restrict the carry forward volume		
Carry forward		This represents the account water that is permitted to be carried forward into the next water year as determined by the carryover rules.		

Table 18: Gwydir held environmental water account summary

Category	Share 30 June	Opening balance	AWD	Drought suspension	on	Assignm	ents	Account usage	End-of-year balance		End-of- year	Carry forward
	2021			In	Out	In	Out		Available	Not Available	forfeit	
General Security	106,617	12,562	61,838	-	-	11,749	5,992	8,604	71,552	0	0	71,552
High Security	5,757	0	5,757	0	0	0	5,757	0	0	0	0	0
Supplementary water	23,591	0	23,591	0	0	22,091	22,091	9,412	14,179	0	14,179	0

Table 19: Annual change summary for Gwydir regulated river environmental licences

Category	Volume 30 June 2020	Volume 30 June 2021	Volume difference	No. Licences 30 June 2020	No. Licences 30 June 2021	No. Licence difference
General Security	106,617	106,617	0	8	8	0
High Security	5,757	5,757	0	4	4	0
Supplementary water	23,591	23,591	0	4	4	0

Table 20: Environmental allocation assignment summary

	Movement of wa	ater via allocation		Ţ	o	
as	ssignments betwe	en consumptive and	Consumptive	Envi	ro	
	environme	ntal licences	General security	neral security		
	Enviro	General security	0	5,992	-	5,992
From	Enviro	High Security	0	5,757	-	5,757
	Enviro	Supplementary	0	-	22,091	22,091
		Total	-	11,749	22,091	33,840

Note 6—Environmental provisions

There are several planned environmental provisions within the regulated Gwydir water source that are implemented under the water sharing plan. These provisions aim to enhance environmental benefits.

A minimum flow requirement through to the Gwydir Wetlands: The flow aims to maintain wetland health by maintaining a minimum flow into the Gwydir Wetlands of up to 500 megalitres per day.

An environmental contingency allowance (ECA): Water is put aside in Copeton storage that can be called upon to achieve environmental benefits such as supporting bird breeding events, supporting native fish colonies and maintaining general river ecosystem health. The amount of water that may be credited to the ECA account is determined based on the available water determinations for General Security licence holders, up to a maximum of 90,000 megalitres. Utilisation of the ECA is managed by the Department of Planning and Environment – Environment, Energy and Science (former New South Wales Office of Environment and Heritage).

Long-term extraction limit: By limiting long-term average extractions to an estimated 392,000 megalitres per year, this plan ensures that approximately 66% of the long-term average annual flow in the water source (estimated to be 1,141,000 megalitres per year) will be preserved and will contribute to the maintenance of basic ecosystem health.

Supplementary access restrictions: During periods of supplementary flow, water made available for consumptive use is restricted to a maximum volume of 50% of the water in excess of requirements, with the remaining 50% being reserved for environmental benefit. For more detail on supplementary water announcements and extractions, refer to Note 18.

Data type

Measured

Policy

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

- Part 3 Environmental Water Provisions
 - Clause 13 and 14 Planned Environmental Water

Available on the NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water

Data accuracy

A1—Nil inaccuracy +/- 0%

Providing agency

NSW Department of Planning and Environment

Data source

WaterNSW/NSW Department of Planning and Environment—Water Accounting System (Joint ownership)

WaterNSW annual compliance report (internal document)

Methodology

The minimum flow required to pass to the Gwydir Wetlands is calculated by assessing the total volume of water entering the Gwydir River from the Horton River, Myall Creek and Hall's Creek

and any water spilling or being pre-released from Copeton Dam against the Yarraman gauge on the Gwydir. The volume assessed up to a maximum of 500 megalitres per day is required to be passed through to Gwydir wetlands being split 50/50 between Gingham and Lower Gwydir. It is however acknowledged that at times when other system requirements are minimal, natural attenuation of flows may mean that the required minimum flows are not achieved. The system operational requirements are indicated in Figure 31 by the total orders at Copeton Dam.


Additional information

Annual accounting information for the ECA is presented in Table 21. Performance of the minimum flow requirement is provided in Figure 35.

Table 21: Summary of ECA account balance¹⁶

Water year	Water credited	Usage	Balance
2009–10	0	0	17,305
2010–11	37,287	5,000	49,610
2011–12	56,890	16,500	90,000
2012–13	2,320	3,074	89,246
2013–14	89,246	1,000	88,246
2014–15	88,246	29,895	58,370
2015–16	2,400	4,750	56,020
2016–17	35,398	21,010	70,408
2017–18	7,922	3,000	75,330
2018–19	0	52,000	23,330
2019–20	1,170	5,228	19,272
2020–21	31,130	7,978	42,424

Figure 35: Plot of minimum flow targets at Yarraman



¹⁶ The ECA balance is held to 4 significant figures only

Note 7—Surface water storage

This is the actual volume of water stored in the individual surface water storages at the date of reporting. The volumes provided represent the total volume of water in the storage, including dead storage, which is the volume of water that cannot be accessed under normal operating conditions (for example, volume below low-level outlet). It is assumed that the dead storage can be accessed if required via alternative access methods (for example syphons).

Data type

Derived from measured data

Policy

Not applicable

Data accuracy

A—Estimated in the range +/- 10%

Providing agency

Lands and Water

Data source

NSW Department of Planning and Environment—HYDSTRA

Methodology

Storage volumes are calculated by processing a gauged storage elevation through a rating table that converts it to a volume.

Additional information

Table 22: Capacity and dead storage summary table

Name	Capacity (ML)	Dead storage (ML)
Copeton Dam	1,361,720	18,490

Note 8—River channel storage

This is the volume of water stored in the river channel on the day of reporting.

Policy

Not applicable

Data type

Derived from measured data

Data accuracy

B—Estimated in the range +/- 25%

Providing agency

NSW Department of Planning and Environment

Data sources

NSW Department of Planning and Environment: HYDSTRA, CAIRO

Methodology

For any river section *i*, the volume of water in the section is:

$$V_i = Q_i \times T_i$$

The river channel storage will be equal to the sum of all river section volumes.

Total river volume
$$=\sum_{i=1}^{n} V_i$$

The components of the above formula are explained in Table 23.

Table 23: Summary of river channel storage calculation components

Symbol	Variable	Data source	Unit
Qi	Average flow in the river section. Calculated by averaging the daily flows at the upstream and downstream river gauges.	HYDSTRA	ML/d
Vi	Volume in each river section	Calculated	ML
Ti	Average travel time for a parcel of water to travel through the river section	CAIRO	days

Assumptions and approximations:

- Travel times are estimated to the nearest day.
- We assume that daily flow change between gauging sites is linear.

Note 9—Storage inflow—Copeton

Storage inflow refers to the volume of water flowing into the major headwater storage, Copeton Dam.

Policy

Not applicable

Data type

Derived from measured data

Data accuracy

A—Estimated in the range +/- 10%

Providing agency

NSW Department of Planning and Environment

Data sources

NSW Department of Planning and Environment: HYDSTRA, SILO (Queensland Government climatic information)

Methodology

In most of the major storages in NSW, there is no direct measurement of inflows. However, it is possible to calculate inflows by using a mass balance approach (based on balancing the change in storage volume) where inflow is the only unknown. This is referred to as a back-calculation of inflows.

The back-calculation figures were derived using a one-day time-step, with the inflow calculated according to the equation below. The daily inflows are then summed to provide an annual inflow figure.

$$I = \sum_{i=1}^{365} \left(\Delta S_i + O_i + Se_i + \frac{(E_i - R_i) * A_i}{100} \right)$$

The components of the above formula are explained in Table 24.

Table 24: Components for back-calculation of inflow

Symbol	Variable	Unit
I	Inflow	ML/day
ΔSi	Change in storage volume at the time i	ML
Oi	Outflow at the time i	ML/day
Sei	Seepage at the time i	ML/day
Ri	Rainfall at the time i	mm/day
Ei	Evaporation (Mortons shallow lake estimation, SILO) at the time i	mm/day
Ai	Surface area at time i —derived from height to surface areas lookup curve	ha

Assumptions and approximations:

- Constant storage specific pan evaporation factors are applied (one annual factor).
- Seepage was assumed to be zero.

Note 10—Storage evaporation and storage rainfall

This refers to the volume of water effective on Copeton Dam that is either lost as a result of evaporation or gained as a result of rainfall.

Data type

Derived from measured data

Policy

Not applicable

Data accuracy

B—Estimated in the range +/- 25%

Providing agency

NSW Department of Planning and Environment

Data source

NSW Department of Planning and Environment—HYDSTRA, SILO (Queensland Government climatic information)

Methodology

Daily rainfall and Mortons shallow lake evaporation data (accessed via SILO) are applied to storage surface area time-series from HYDSTRA to achieve a volume in megalitres that is then aggregated to an annual figure. The rainfall and evaporation data used is equivalent to the data used in the storage inflow back-calculation (Note 9)

Rainfall:

$$\mathbf{V} = \sum_{i=0}^{365} \left(\frac{R_i \times A_i}{100} \right)$$

Evaporation:

$$\mathbf{V} = \sum_{i=0}^{365} \left(\frac{E_i \times \mathbf{A}_i}{100} \right)$$

The components of the above formulas are explained in Table 25.

Table 25: Components for storage evaporation and rainfall

Symbol	Variable	Unit
V	Volume	ML/year
Ri	Rainfall at the time i	mm/day
Ai	Surface area at the time i—derived from height to surface areas lookup curve	На
Ei	Evaporation (Mortons shallow lake estimation, SILO) at the time i	mm/day

Note 11—River evaporation and river rainfall

This refers to the volume of water effective on the accounted river reach that is either lost as a result of evaporation or gained as a result of rainfall.

Data type

Derived from measured data

Policy

Not applicable

Data accuracy

C—Estimated in the range +/- 50%

Providing agency

NSW Department of Planning and Environment

Data source

NSW Department of Planning and Environment: HYDSTRA, ARCGIS

QLD Department of Natural Resources: SILO

Methodology

The volume applied for evaporation and rainfall on the regulated river is achieved by first calculating a daily time-series of river area. This is achieved by breaking the river up into reaches and utilising the cross sections recorded at river gauging locations to determine the average width of the river with a given daily flow. River length is then determined between 2 gauging locations using ARCGIS and as such an area for each reach can be defined.

Area
$$(m^2)$$
 = Average W (m) x L (m)

In the formula, W is the daily width determined from the gauging cross sections and L is the length as determined through ARCGIS analysis.

With daily area determined, various climate stations are then selected based on their proximity to each river reach. Rainfall and evaporation data is then extracted from SILO and applied to the area time-series to achieve a volume in megalitres that is then aggregated to an annual figure.

Rainfall:

$$V = \sum_{i=1}^{365} \frac{R_i \times A_i}{10^6}$$

Evaporation:

$$V = \sum_{i=1}^{365} \frac{ETO_i \times K_c \times A_i}{10^6}$$

The components of the above formulas are explained in Table 26.

Table 26: Components for storage evaporation and rainfall

Symbol	Variable	Unit
V	Volume	ML/year
R	Rainfall	mm/day
Ai	Surface area at the time i—derived from height to surface areas lookup curve	m ²
ETOi	Reference evapotranspiration from SILO at the time i	mm/day
Kc	Crop coefficient for open water (1.05)	-

Note 12—Gauged tributary inflow

This is the inflow into the regulated river that occurs downstream of the headwater storages and is measured at known gauging stations.

Policy

Not applicable

Data type

Measured data

Data accuracy

A—Estimated in the range +/- 10%

Providing agency

NSW Department of Planning and Environment

Data sources

NSW Department of Planning and Environment: HYDSTRA

Methodology

The flows are obtained by measuring river heights at gauging stations along the river, and then passing these heights through a rating table that converts them to a daily flow volume.


Additional information

The total gauged inflow for the reporting period is the sum of the inflows for the gauged tributaries defined in Table 27. A plot of the daily gauged tributary inflows is provided in Figure 36.

Table 27: Summary of gauged tributary inflow (annual volume in megalitres)

Station	Station name	Catchment area (km²)	Inflow (ML)
418025	Halls Creek at Bingara	156	3,059
418015	Horton River at Rider	1,970	342,334
418017	Myall Creek at Molroy	842	69,191
418032	Tycannah Creek at Horseshoe Lagoon	866	83,695
416054	Gil Gil Creek at Boolataroo		89,048
		Total Gauged Inflow	587,328

Figure 36: Gauged tributary Inflow



Note 13—Ungauged runoff estimate

This is the inflow into the river that occurs downstream of the headwater storages and is not measured.

Policy

Not applicable

Data type

Estimated

Data accuracy

C-Estimated in the range +/- 50%

Providing agency

NSW Department of Planning and Environment

Data sources

NSW Department of Planning and Environment, HYDSTRA

Methodology

To derive an estimate, a simple mass balance approach was adopted between Copeton Dam and Pallamallawa, whereby known inflows and outflows were combined with an assumed loss factor.

$$UI = EoS - SR - GI + E + LE$$

Where:

UI = Ungauged inflow estimate

EoS = Gauged flow at the point in the system where no further inflow is estimated downstream for the purposes of this ungauged calculation (Pallamallawa).

SR_k = Copeton storage release

GI = Gauged inflows (Copeton to Pallamallawa)

E = Extractions (Copeton to Pallamallawa)

LE = Estimated losses. This was assumed to be 10% of the measured (gauged flow plus storage releases) entering the system.

Additional information

For 2019–20, an additional estimate of 8,000 megalitres was included to estimate additional ungauged inflows in the Moomin Creek system (downstream of Pallamallawa).

Table 28 summarises ungauged inflow estimates for the reporting period and prior years.

Table 28: Summary of Gwydir ungauged inflow estimates

Catchment	Total volume estimated (ML)		
2013-14	49,000		
2014-15	52,000		
2015-16	65,000		
2016-17	196,000		
2017-18	120,000		
2018-19	2,000		
2019-20	67,000 ¹⁷		
2020-21	233,000		

¹⁷ Includes 8,000 megalitres Moomin Creek

Note 14—Dam releases, river inflow from dam releases

This the volume of water released from Copeton Dam. In the accounting process, this release is represented as both a decrease in asset (of the dam) and an equal increase in asset (of the river).

Policy

Not applicable

Data type

Measured data

Data accuracy

A—Estimated in the range +/- 10%

Providing agency

NSW Department of Planning and Environment

Data sources

NSW Department of Planning and Environment: HYDSTRA


Methodology

The flows are obtained by measuring river heights at a gauging station downstream of the dam wall, and then passing these heights through a rating table that converts them to a daily flow volume. The releases have been represented in the Statement of Changes in Water Assets and Water Liabilities as both a decrease in water asset (water leaving the dam) and an equal volume of increase in water asset (water released increasing the volume of the river).

Additional information

Figure 37 provides daily releases from Copeton storage for the reporting period.

Figure 37: Copeton Dam releases



Note 15—End-of-system flow/flow to wetlands/replenishments

This refers to flow that leaves the entity and does not return to the entity. The flow has been separated into delivered replenishment flows that are delivered as a requirement of the water sharing plan and other end-of-system flows. The *flow to wetlands* line item (effectively an end-of-system flow for accounting purposes) is an estimate of the total amount of water that entered the Gwydir wetlands.

Under the conditions of the water sharing plan, water must be put aside in Copeton dam to deliver, as required, replenishment flows of up to 21,000 megalitres, broken down into the following 5 specific areas:

- 6,000 megalitres per year to the Gingham Watercourse—this is no longer required due to the completion of the lower Gingham Domestic Water Supply Scheme in April 2011
- 4,000 megalitres per water year to the lower Gwydir system—this is no longer required due to the completion of the lower Gingham Domestic Water Supply Scheme in June 2013
- up to 6,000 megalitres per water year to Mallowa Creek. This flow is no longer required due to the completion of the Mallowa/Ballinboora Creek Water Efficiency Scheme
- up to 4,000 megalitres per water year to Thalaba Creek
- up to 1,000 megalitres per water year to Ballin Boora Creek. This flow is no longer required due to the completion of the Mallowa/Ballinboora Creek Water Efficiency Scheme

Data type

Derived from measured data

Policy

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

- Part 12 System operation rules
 - Clause 58 Replenishment flows

Available on the NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water

Data accuracy

A—Estimated in the range +/- 10%

Providing agency

NSW Department of Planning and Environment

Data source

NSW Department of Planning and Environment—HYDSTRA, WaterNSW annual compliance report (internal document)

Methodology

End-of-system flows are derived by the summation of flows at gauging site/s measuring the volume of water that leaves the accounting extent (Figure 1). Replenishments flows are obtained from the annual WaterNSW compliance reports.

Flows to the Gwydir wetlands are estimated by summating flows leaving Tyreel weir (which is passed to both to the lower Gwydir River and Gingham watercourse), and then subtracting any non-environmental usage from these reaches below Tyreel weir. The remaining volume is assumed to be the amount that was supplied to the Gwydir wetlands.

Additional information

A summary of the calculation to determine the inflow to wetlands line item is presented in Table 29. Total end-of-system flows for the reporting period are summarised in Table 30. End-of-system outflows, excluding the flow to wetlands, are illustrated in Figure 38.

Table 29: Calculation of Gwydir flow to wetlands

Component	Volume (ML)
Gingham watercourse diversion from Tyreel Weir	232,342
less Consumptive usage from Gingham watercourse below Tyreel Weir	(4,958)
plus Gwydir River release from Tyreel Weir	92,480
less Consumptive usage from Gwydir River below Tyreel Weir	(21,313)
Total volume estimate flow delivered to the Gwydir wetlands	298,552
Replenishment component of flow to wetlands	018


Table 30: End-of-system flow summary

Station	Volume (ML)	Accounting component
Mehi River at Bronte ¹⁹	106,951	End of system: other
Moomin Creek at Moomin Plains ¹⁹	62,191	End of system: other
Gil Gil Creek at Galloway	99,411	End of system: other
Replenishment outflows	0	End of system: replenishment
Total end of system flow	268,553	-

¹⁸ Replenishment supplies to the Lower Gwydir and Gingham are no longer supplied from open channel deliveries due to completion of the domestic and stock supply pipeline scheme

¹⁹ Flow recorded at Mehi River near Collarenebri (traditionally used in GPWAR), was impacted by large flows in the Barwon Darling during 2020–21 and not suitable for quantifying outflows from the Mehi. The next upstream gauge, Mehi at Bronte was therefore used for this GPWAR. When using this gauge Moomin Creek outflow is also required to be quantified, which has been assumed as the measured flow at gauge 418070.

Figure 38: Gwydir end of system (excludes flow to wetlands)



Note 16—Extractions from river

This is the volume of water directly pumped or diverted from the regulated river by licence holders.

Occasionally (generally in the case of environmental water) volumes are ordered against a licence account for in-stream benefits or to pass through end-of-system target points. As such, the volume reported to be physically extracted from the accounted river extent will not always be equal to the amount of water debited against accounts for usage, which has been described in Note 3. The figure stated for extractions from river excludes basic rights extractions, which is reported as a separate line item and detailed in Note 17.

Data type

Measured data

Policy

Not applicable

Data accuracy

A—Estimated in the range +/- 10%

Providing agency

NSW Department of Planning and Environment

Data source

WaterNSW/NSW Department of Planning and Environment—Water Accounting System.

NSW Department of Planning and Environment—Water Ordering and Usage database

Methodology

For the purposes of this GPWAR, extraction from the river is considered to be the total volume metered and debited to the allocation accounts, minus any licenced account water that can be identified as being used within the system or ordered to be passed through the system. These volumes are generally associated with environmental water orders and have already been accounted for separately in other line items.

Additional information

Table 31 reconciles estimated extractions from the river compared to total account usage.

Table 31: Reconciliation of physical extraction to account usage

Component	Volume (ML)
Licenced extractions from river ²⁰	202,432
Plus	
Licensed flow leaving system ²¹	0
Plus	
In-stream licenced usage ²²	0
equals	
Total allocation account usage ²³	202,432

²⁰ Direct licensed extractions from the river excluding basic rights usage estimate

²¹ Licenced water ordered to leave the accounted Gwydir extent for environmental benefits

²² Water ordered and used within the accounted system for environmental benefit (not extracted from river)

²³ The total amount of water accounted for usage against the allocation accounts

Note 17—Basic rights extractions

This is the non-licensed right to extract water to meet basic requirements for household purposes (non-commercial uses in and around the house and garden) and for watering of stock. It is available for anyone who has access to river frontage on their property.

This water cannot be used for irrigating crops or garden produce that will be sold or bartered, for washing down machinery sheds or for intensive livestock operations.

In times of limited supply, there may be restrictions on taking water for domestic and stock use.

Data Type

Estimated

Policy

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

- Part 4 Basic Landholder Rights
 - Clause 17 Domestic and stock rights

Available on the NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water

Data accuracy

C—Estimated in the range +/- 50%

Providing agency

NSW Department of Planning and Environment

Data source

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

Methodology

The estimation of domestic and stock rights uses a series of estimates for water usage, stocking rates, population and property shape based on local knowledge to calculate riparian (Stock and Domestic) requirements in megalitres per year. The annual extraction for Domestic and Stock rights in the water accounts is assumed to be the estimated figure stated in the *Water Sharing Plan for the Gwydir Regulated River Water Source 2016* (6,000 megalitres)

Note 18—Supplementary extractions

This is the volume of water extracted or diverted under Supplementary access licences during announced periods of supplementary water. Supplementary flow events are announced periodically during the season when high flow events occur, with the period of extraction and volume of water to be extracted determined based on the rules as set out in the water sharing plans. Supplementary access licences differ from other categories in that the volume of water in the account refers to an annual upper limit for extractions and its provision is totally reliant on the occurrence of high flow events.

Data type

Measured data

Policy

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

- Part 8 Limits to the availability of water
 - o Division 2—Available water determinations
 - Clause 38 Available water determinations for supplementary water access licences
- Part 9 Rules for managing access licences
 - o Division 3—Extraction conditions
 - Clause 47 Taking of water under supplementary water access licences

Refer to applicable Water Sharing Plan on the NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water

Data accuracy

Estimated in the range +/- 10%

Providing agency

NSW Department of Planning and Environment

Data source

WaterNSW/NSW Department of Planning and Environment—Water Accounting System (joint ownership)

Methodology

Supplementary water extraction and diversion data is collected by either on-farm meters that measure extraction or gauges on diversion works. Meter readings are collected for individual licence holders at intervals during the year and converted via a calibration factor to a volume of water extracted. Water diverted from the river is measured by recording the height at either the gauge or weir, with the volume diverted being derived by passing these heights through a rating table. However, with supplementary water being extracted through the same pumps as those extracting water under other categories of access licences, more information is needed to separate out supplementary extraction. Basically, licence holders notify us of their intention to pump before pumping or diverting water during the declared supplementary event. They also provide meter readings both at the start and end of pumping. This enables the supplementary flow extraction to be assessed independently of other categories of access licences.

The total volume of water that may be made available for extraction under supplementary water access licences in the Gwydir Regulated River Water Source should not exceed 50% of the total supplementary volume available to share (remaining 50% reserved for environmental benefits).

Additional information

Daily supplementary extractions, totals extraction by river section and operational supplementary announcements are presented in Figure 39, Figure 40 and Table 32 respectively.

Figure 39: Supplementary daily extractions




Figure 40: Total supplementary usage by river section




Table 32: Gwydir supplementary announcements

Announce date	% use limit	Section	Section start date	Section end date	Supp. usage
17-Dec-20	30	Copeton to Bingara	17-Dec-20	31-Dec-20	0
17-Dec-20	30	Bingara to Gravesend	17-Dec-20	31-Dec-20	0
17-Dec-20	30	Gravesend to Pallamallawa	17-Dec-20	31-Dec-20	0
17-Dec-20	30	Pallamallawa to Tareelaroi	17-Dec-20	31-Dec-20	105.2
17-Dec-20	25	Tareelaroi to Boolooroo	17-Dec-20	31-Dec-20	3364.3
17-Dec-20	25	Boolooroo to Yarraman	17-Dec-20	31-Dec-20	0
17-Dec-20	25	Yarraman to Tyreel Weir	17-Dec-20	31-Dec-20	459.2
17-Dec-20	25	Tyreel Weir to Gwydir Pool	17-Dec-20	31-Dec-20	356
17-Dec-20	25	Tyreel Anabranch	17-Dec-20	31-Dec-20	0
17-Dec-20	20	Tyreel/Reg to Morcott	18-Dec-20	25-Dec-20	138.7
17-Dec-20	20	Morcott to Brageen	18-Dec-20	25-Dec-20	1702
17-Dec-20	20	Tyreel to Morcott	18-Dec-20	25-Dec-20	0
17-Dec-20	25	Brageen to Allambi	17-Dec-20	30-Dec-20	1159.4
17-Dec-20	20	Allambi to Millewa	17-Dec-20	31-Dec-20	637.3
17-Dec-20	20	Millewa to Wandoona	17-Dec-20	31-Dec-20	269
17-Dec-20	25	Combadello to Romani	17-Dec-20	25-Dec-20	932.3
17-Dec-20	25	Romani to Glendell0	17-Dec-20	25-Dec-20	677.8
17-Dec-20	25	Glendello to Chesney	17-Dec-20	26-Dec-20	1598.5
17-Dec-20	25	Chesney to Clarendon	17-Dec-20	26-Dec-20	252.4
17-Dec-20	25	Clarendon to Wirrillah	17-Dec-20	1-Jan-21	840.5
17-Dec-20	25	Wirrillah to Alma	17-Dec-20	1-Jan-21	251.5
17-Dec-20	30	Alma to Iffley	17-Dec-20	7-Jan-21	4966.8
17-Dec-20	30	Iffley to Oreal	17-Dec-20	7-Jan-21	0
18-Dec-20	15	Boolooroo to Midkin	18-Dec-20	31-Dec-20	1955.7
18-Dec-20	15	Midkin to Lagoon	18-Dec-20	31-Dec-20	303
18-Dec-20	15	Lagoon Garah Br	18-Dec-20	31-Dec-20	1086.8
18-Dec-20	30	Combadello to Yamba	18-Dec-20	31-Dec-20	4348.6
18-Dec-20	30	Yamba to Gundare	18-Dec-20	31-Dec-20	3748
19-Dec-20	25	Garah Br to Gil Gil Junc	19-Dec-20	4-Jan-21	4067
19-Dec-20	50	Gundare to Kurrabooma	20-Dec-20	4-Jan-21	617.9
19-Dec-20	50	Kurrabooma to Ballinboora	20-Dec-20	4-Jan-21	1178
19-Dec-20	50	Ballinboora to Bronte	20-Dec-20	4-Jan-21	0
19-Dec-20	50	Bronte to Myambla	20-Dec-20	4-Jan-21	0
20-Dec-20	50	Gil Gil Junc to Rio Grand	20-Dec-20	5-Jan-21	842
20-Dec-20	50	Rio Grande to Cleveland	20-Dec-20	5-Jan-21	2361.1
22-Dec-20	25	Tareelaroi to Moree	22-Dec-20	28-Dec-20	0
22-Dec-20	25	Moree to Combadello	22-Dec-20	28-Dec-20	1256.4
4-Jan-21	5	Pallamallawa to Tareelaroi	4-Jan-21	7-Jan-21	56.1
4-Jan-21	5	Tareelaroi to Boolooroo	4-Jan-21	7-Jan-21	758.2
4-Jan-21	5	Boolooroo to Yarraman	4-Jan-21	7-Jan-21	0

Announce date	% use limit	Section	Section start date	Section end date	Supp. usage
4-Jan-21	5	Yarraman to Tyreel Weir	4-Jan-21	7-Jan-21	92.2
4-Jan-21	5	Tyreel/Reg to Morcott	4-Jan-21	7-Jan-21	34.7
4-Jan-21	5	Morcott to Brageen	4-Jan-21	7-Jan-21	424
4-Jan-21	5	Tyreel Weir to Gwydir Pool	4-Jan-21	7-Jan-21	84.3
4-Jan-21	5	Tyreel Anabranch	4-Jan-21	7-Jan-21	0
4-Jan-21	5	Tyreel to Morcott	4-Jan-21	7-Jan-21	0
28-Feb-21	20	Copeton to Bingara	28-Feb-21	5-Mar-21	0
28-Feb-21	20	Bingara to Gravesend	28-Feb-21	5-Mar-21	0
28-Feb-21	20	Gravesend to Pallamallawa	28-Feb-21	5-Mar-21	54
28-Feb-21	20	Pallamallawa to Tareelaroi	28-Feb-21	5-Mar-21	258.9
28-Feb-21	10	Tareelaroi to Boolooroo	28-Feb-21	2-Mar-21	2315.8
28-Feb-21	10	Boolooroo to Yarraman	28-Feb-21	2-Mar-21	0
28-Feb-21	10	Yarraman to Tyreel Weir	28-Feb-21	2-Mar-21	183.5
28-Feb-21	10	Tyreel Weir to Gwydir Pool	28-Feb-21	2-Mar-21	168.4
28-Feb-21	10	Tyreel Anabranch	28-Feb-21	2-Mar-21	0
28-Feb-21	5	Tyreel/Reg to Morcott	1-Mar-21	4-Mar-21	34.8
28-Feb-21	5	Morcott to Brageen	1-Mar-21	4-Mar-21	452
28-Feb-21	5	Brageen to Allambi	1-Mar-21	4-Mar-21	231.5
28-Feb-21	5	Allambi to Millewa	1-Mar-21	4-Mar-21	162.9
28-Feb-21	5	Millewa to Wandoona	1-Mar-21	4-Mar-21	67.3
28-Feb-21	10	Tareelaroi to Moree	1-Mar-21	3-Mar-21	0
28-Feb-21	10	Moree to Combadello	1-Mar-21	3-Mar-21	508.2
1-Mar-21	10	Combadello to Yamba	2-Mar-21	6-Mar-21	1146.5
1-Mar-21	10	Yamba to Gundare	2-Mar-21	6-Mar-21	1584.9
1-Mar-21	5	Gundare to Kurrabooma	1-Mar-21	8-Mar-21	211.6
1-Mar-21	5	Kurrabooma to Ballinboora	1-Mar-21	8-Mar-21	118
1-Mar-21	5	Ballinboora to Bronte	1-Mar-21	8-Mar-21	0
1-Mar-21	5	Bronte to Myambla	1-Mar-21	8-Mar-21	0
1-Mar-21	5	myambla to colly	1-Mar-21	8-Mar-21	0
1-Mar-21	10	Boolooroo to Midkin	1-Mar-21	6-Mar-21	1620.8
1-Mar-21	10	Midkin to Lagoon	1-Mar-21	6-Mar-21	101
1-Mar-21	10	Lagoon Garah Br	1-Mar-21	6-Mar-21	566.9
1-Mar-21	5	Glendello to Chesney	1-Mar-21	3-Mar-21	319.7
1-Mar-21	5	Chesney to Clarendon	1-Mar-21	3-Mar-21	96
1-Mar-21	10	Clarendon to Wirrillah	1-Mar-21	6-Mar-21	335.9
1-Mar-21	10	Wirrillah to Alma	1-Mar-21	6-Mar-21	101
2-Mar-21	8	Garah Br to Gil Gil Junc	2-Mar-21	7-Mar-21	1179.5
10-Mar-21	100	Boolooroo to Midkin	10-Mar-21	17-Apr-21	5636.2
10-Mar-21	100	Midkin to Lagoon	10-Mar-21	24-Apr-21	332.4
10-Mar-21	100	Lagoon Garah Br	10-Mar-21	24-Apr-21	6573.3
10-Mar-21	100	Garah Br to Gil Gil Junc	10-Mar-21	17-Apr-21	7366.2

Announce date	% use limit	Section	Section start date	Section end date	Supp. usage
10-Mar-21	100	Gil Gil Junc to Rio Grand	10-Mar-21	2-May-21	2215.6
10-Mar-21	100	Combadello to Romani	10-Mar-21	10-Apr-21	702.1
10-Mar-21	100	Romani to Glendell0	10-Mar-21	10-Apr-21	0
10-Mar-21	100	Alma to Iffley	10-Mar-21	10-Apr-21	8929.6
10-Mar-21	100	Iffley to Oreal	10-Mar-21	10-Apr-21	0
11-Mar-21	100	Tyreel/Reg to Morcott	11-Mar-21	10-Apr-21	49.4
11-Mar-21	100	Morcott to Brageen	11-Mar-21	10-Apr-21	2859.6
11-Mar-21	100	Tyreel Weir to Gwydir Pool	11-Mar-21	10-Apr-21	190
11-Mar-21	100	Rio Grande to Cleveland	11-Mar-21	5-May-21	6116.5
11-Mar-21	100	Glendello to Chesney	11-Mar-21	12-Apr-21	2293.8
11-Mar-21	100	Chesney to Clarendon	11-Mar-21	12-Apr-21	379.9
11-Mar-21	100	Clarendon to Wirrillah	11-Mar-21	12-Apr-21	782.5
11-Mar-21	100	Wirrillah to Alma	11-Mar-21	12-Apr-21	269
12-Mar-21	100	Tareelaroi to Boolooroo	12-Mar-21	10-Apr-21	5097.1
12-Mar-21	100	Allambi to Millewa	12-Mar-21	17-Apr-21	2157.1
12-Mar-21	100	Millewa to Wandoona	12-Mar-21	17-Apr-21	1010
15-Mar-21	100	Tareelaroi to Moree	15-Mar-21	10-Apr-21	0
15-Mar-21	100	Moree to Combadello	15-Mar-21	10-Apr-21	1257
15-Mar-21	100	Combadello to Yamba	18-Mar-21	10-Apr-21	8368.1
15-Mar-21	100	Yamba to Gundare	18-Mar-21	10-Apr-21	4673
15-Mar-21	100	Gundare to Kurrabooma	18-Mar-21	10-Apr-21	380.5
15-Mar-21	100	Kurrabooma to Ballinboora	18-Mar-21	10-Apr-21	706.1
15-Mar-21	100	Bronte to Myambla	18-Mar-21	10-Apr-21	0
15-Mar-21	100	Copeton to Bingara	15-Mar-21	10-Apr-21	0
15-Mar-21	100	Bingara to Gravesend	15-Mar-21	10-Apr-21	0
15-Mar-21	100	Gravesend to Pallamallawa	15-Mar-21	10-Apr-21	27.4
15-Mar-21	100	Pallamallawa to Tareelaroi	15-Mar-21	10-Apr-21	146.5
15-Mar-21	100	Boolooroo to Yarraman	15-Mar-21	10-Apr-21	0
15-Mar-21	100	Yarraman to Tyreel Weir	15-Mar-21	10-Apr-21	734
15-Mar-21	100	Tyreel Weir to Gwydir Pool	15-Mar-21	10-Apr-21	204.7
16-Mar-21	100	Brageen to Allambi	16-Mar-21	10-Apr-21	3246.7
11-Jun-21	100	Copeton to Bingara	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Bingara to Gravesend	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Gravesend to Pallamallawa	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Pallamallawa to Tareelaroi	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Tareelaroi to Boolooroo	11-Jun-21	30-Jun-21	762.1
11-Jun-21	100	Boolooroo to Yarraman	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Yarraman to Tyreel Weir	11-Jun-21	30-Jun-21	768.3
11-Jun-21	100	Tyreel/Reg to Morcott	11-Jun-21	30-Jun-21	54.6
11-Jun-21	100	Morcott to Brageen	11-Jun-21	30-Jun-21	714.2
11-Jun-21	100	Brageen to Allambi	11-Jun-21	30-Jun-21	0

Announce date	% use limit	Section	Section start date	Section end date	Supp. usage
11-Jun-21	100	Allambi to Millewa	11-Jun-21	30-Jun-21	202
11-Jun-21	100	Millewa to Wandoona	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Lower Gwydir (replenishment)	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Boolooroo to Midkin	11-Jun-21	30-Jun-21	751.9
11-Jun-21	100	Midkin to Lagoon	11-Jun-21	30-Jun-21	502
11-Jun-21	100	Lagoon Garah Br	11-Jun-21	30-Jun-21	1497
11-Jun-21	100	Garah Br to Gil Gil Junc	11-Jun-21	30-Jun-21	2140.5
11-Jun-21	100	Gil Gil Junc to Rio Grand	11-Jun-21	30-Jun-21	309
11-Jun-21	100	Rio Grande to Cleveland	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Tyreel Weir to Gwydir Pool	11-Jun-21	30-Jun-21	199.2
11-Jun-21	100	Tareelaroi to Moree	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Moree to Combadello	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Combadello to Yamba	11-Jun-21	30-Jun-21	410.7
11-Jun-21	100	Yamba to Gundare	11-Jun-21	30-Jun-21	2252.8
11-Jun-21	100	Gundare to Kurrabooma	11-Jun-21	30-Jun-21	2927
11-Jun-21	100	Kurrabooma to Ballinboora	11-Jun-21	30-Jun-21	40.1
11-Jun-21	100	Ballinboora to Bronte	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Bronte to Myambla	11-Jun-21	30-Jun-21	0
11-Jun-21	100	myambla to colly	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Combadello to Romani	11-Jun-21	30-Jun-21	34.3
11-Jun-21	100	Romani to Glendell0	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Glendello to Chesney	11-Jun-21	30-Jun-21	1817.6
11-Jun-21	100	Chesney to Clarendon	11-Jun-21	30-Jun-21	424.4
11-Jun-21	100	Clarendon to Wirrillah	11-Jun-21	30-Jun-21	468.9
11-Jun-21	100	Wirrillah to Alma	11-Jun-21	30-Jun-21	385
11-Jun-21	100	Alma to Iffley	11-Jun-21	30-Jun-21	3137.6
11-Jun-21	100	Iffley to Oreal	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Tyreel Anabranch	11-Jun-21	30-Jun-21	0
11-Jun-21	100	Tyreel to Morcott	11-Jun-21	30-Jun-21	0

Note 19—Unaccounted difference

In theory, if all the processes of a water balance could be accurately accounted for, the unaccounted difference would be zero. In reality, because of uncertainty about many of the volumes presented in the accounts, the variety of data sources, and not all processes of the water cycle being accounted for, the statements are not balanced at the end of the accounting process. To balance the accounts, a final balancing entry is required, and this is termed the unaccounted difference. As technology improves the accuracy of the account estimates, we anticipate that, relatively, this figure should be lower in future accounts.

Data type

Not applicable

Policy

Not applicable

Data accuracy

D—Estimated in the range +/- 100%

Providing agency

Not applicable

Data source

Not applicable

Methodology

The unaccounted difference is equal to the amount needed to get the correct volume in river at the end of the reporting period, after all the known physical inflows and outflows have been accounted for. The double-entry accounting process attempts to represent the physical movement of water by creating a river asset. The opening and closing balance of the river volume was estimated according to Note 8.

Surface Water Unaccounted difference

$$UVSW = Rs - Rc + RI - Ro$$

Where:

UVSW = Unaccounted difference for Surface Water

Rs = Opening river volume estimate

Rc = Closing river volume estimate

Ro = Physical outflows from the river (for example, extractions)

RI = Physical inflows to the river (for example, runoff, return flows, dam releases)

Additional information

The unaccounted difference as a percentage of total river inflow for the reporting period and prior years is presented in Table 33.

Table 33: Summary of unaccounted difference

Water year	Unaccounted difference (ML)	Total river inflow (ML) ²⁴	% of inflow
2013–14	67,972	670,354	10%
2014–15	5,701	405,337	1%
2015–16	4,958	273,707	2%
2016–17	51,699	774,000	7%
2017–18	142,421	585,358	24%
2018–19	69,664	261,611	27%
2019–20	7,287	165,958	4%
2020-21	265,160	926,388	29%

²⁴ Total river inflows as presented in the water accounting statements

Note 20—River and groundwater interaction

This note refers to water that has been identified as either flowing from the connected alluvium to the accounted river extent (increase in water asset), or alternatively from the accounted river extent to the alluvium aguifer (decrease in water asset).

Data type

Modelled

Policy

Not applicable

Data accuracy

D—Estimated in the range +/- 100%

Providing agency

NSW Department of Planning and Environment

Data source

NSW Department of Planning and Environment—MODFLOW (Data inputs from HYDSTRA, GDS)

Methodology

For the lower Macquarie groundwater source the method used to calculate either flow from the connected alluvium to the accounted river extent and the accounted river extent to the alluvium aquifer can be either of the following:


- If available use the estimated annual budget from the NSW Department of Planning and Environment MODFLOW model for the lower Gwydir groundwater source (see Method A in the document NSW General Purpose Water Accounting Reports—Groundwater Methodologies, available for download from the NSW Department of Planning and Environment website at www.industry.nsw.gov.au/water).
- Alternatively, an estimation based on the relationships developed between the flow at river gauging site '418002 Mehi River at Moree' and historical MODFLOW model results. The resulting equations used for estimating the accounting inputs are as follows:
 - o Inflow to River from Aquifer = (Annual Flow Moree − 98,139)/109.26
 - River Outflow to Aquifer = (8,600 'Inflow to River from Aquifer')/ 0.375

No estimates were made for interactions with the river outside the area covered by the lower Gwydir groundwater source.

Additional information

Spatial coverage of the modelling data relative to the Gwydir catchment is presented in Figure 41. Groundwater interaction with the river outside of this area would form part of the unaccounted difference volume reported in the statements. The modelled annual groundwater budget for the reporting period was not available at the time of writing and any volumes associated with ground water interactions are included in the unaccounted difference shown in Table 33.

Figure 41: Groundwater methods



Note 21—Water order debiting

In the Gwydir regulated water source the allocation accounts are currently managed using a water order debiting approach. Accounting under this system defines that the accounts are reduced by the greater of the volume of water:

- extracted
- ordered for extraction against an access licence.

Therefore, the volume appearing in statements against the line item 'water order debiting' reflects the amount of water ordered against a category of licence that is in excess of the physical extraction that occurred.

Data type

Measured/calculated

Policy

Water Sharing Plan for the Gwydir Regulated River Water Source 2016

- Part 9—Rules for managing access licences.
 - o Division 2—Water allocation account management.
 - Clause 42—Volume taken under access licences.

Available on the NSW Department of Planning and Environment website at https://www.industry.nsw.gov.au/water

Data accuracy

Estimated in the range +/- 10%.

Providing agency

NSW Department of Planning and Environment

Data source

WaterNSW/NSW Department of Planning and Environment—Water accounting system (joint ownership)

Methodology

Over-order debiting is a required component of balancing the allocation accounts detailed in Note 1. The over-order debit component is calculated by analysing the recorded extractions against orders for the corresponding measurement period. That is, if metered usage is collected monthly, then the corresponding monthly orders are compared and any orders that are in excess the usage are recorded as over-order debit.

Note 22—Adjusting entry

This is a line item that is used to correct balances in the accounts. The double entry accounting being applied is a continuous process whereby the closing balance of one year is the opening balance for the following year.

Occasionally, we need to correct accounts for a variety of reasons including when we have identified an error in the previous year's reporting, a balance in the previous year has since been adjusted, or when a process that had previously been reported cannot be supplied and the associated asset or liability must be removed to maintain the integrity of the statements.

This is different to the unaccounted difference component, which is a physical volume required to achieve mass balance after all the known processes have been accounted.

Data type

Calculated

Accuracy

A1-Nil inaccuracy +/- 0%

Providing agency

NSW Department of Planning and Environment

Data source

Not applicable

Methodology

A journal entry is placed in the comparative year to ensure correct opening balances are achieved in the reporting year. No adjusting entries were needed for the reporting period.

References

WASB 2012, Australian Water Accounting Standard 1 Preparation and Presentation of General Purpose Water Accounting Reports (AWAS 1), Bureau of Meteorology